BROWNELLS UNIVERSAL REAR SIGHT **ELEVATOR KIT**

24 Of The Most Popular Elevators

Universal Elevator Kit contains 24 elevators, covering the most common ones you get calls for. Included are six double-step short elevators: 6 double-step long elevators: 6 standard width (.080") single-step elevators and six special narrow width (.050") singlestep elevators. Don't pass this kit up - a real money maker and lifesaver for any





| SPECS: Length and | width varies. Blued steel. | /, |
|-------------------|----------------------------|------------------------|
| STOCK# | QUANTITY | FITS |
| #080-506-001 | 6 | .080" wide single-step |
| #080-506-002 | 6 | .050" wide single-step |
| #080-506-003 | 6 | short double-step |
| #080-506-004 | 6 | long double-step |

| - Advise # - | Sight Elevator Refill, 8K8N99 \$ 11.99 | |
|--------------|---|--|
| #080-506-000 | Rear Sight Elevator Kit, 8K27l19 \$ 33.99 | |



Not just another slot-filler, but an attractive, all steel blank that hides the unsightly appearance of an empty sight dovetail on your favorite sporter rifle. Stylish, diamond shape with decorative, milled edges blends naturally into the barrel contour for a truly finished look. Polished and blued with enough room for custom engraving, if so desired. Fits standard, .375" x 60° dovetails without fitting. SPECS: Steel, polished blue finish. 1" (2.5cm) long x 9/16" (1.4cm) wide. Fits .375" x 60° dovetail.

#080-000-193 Decorative Slot Blank, 8K16Q14......\$ 18.99

BROWNFLLS SIGHT DOVETAIL SLOT BLANK

Fill Empty Dovetails For A Clean, **Finished Appearance**

The perfect cure when removing factory sights or restoring antiques to original space. Mild steel blanks machined

slightly oversize for a close, perfectly blended fit in barrel sight dovetails. Easy to shape, file and blue. SPECS: Mild steel, blued finish. 12" (30.4cm) long, fits nominal 3/8 (9.52mm) x 60° dovetails

#080-770-375 Dovetail Slot Blanks, 8K14B44 \$ 16.99



MARBLE **NO. 87 SLOT BLANK**

Ready-Made To Fill Sight Dovetails

Polished blue or matte stainless steel, flat top blank fills empty sight dovetails.

SPECS: Carbon steel, blued, polished, or stainless steel, matte finish. Fits nominal 3/8" (9.5mm), 60° dovetails. Approximately 5/8" (15.8mm) wide overall.

#579-087-100 No. 87 Dovetail Slot Blank, Blued, 9G6C74 . . \$ 8.99 #579-000-014 No. 87 Dovetail Slot Blank, SS, 9G8/24 ... 10.99

WILLIAMS ALUMINUM SLOT BLANK

Fills Empty Sight Dovetail Without Fitting

Machined, aluminum, slot blank dropsin easily to fill the empty sight dovetail for a clean-looking barrel. 5-40 set screw locks

blank in place and makes removal easy. Black anodized to blend well with most blue finishes. SPECS: Aluminum, black anodized, 3/8" (9.5mm) x 5/8" (15.9mm), Fits stan-

dard, .375" (9.5mm) x 60° dovetails.

#962-000-034 Aluminum Slot Blank, 2F5L59......\$ 6.99

HIVIZ FIBER OPTIC RIFLE SIGHT

Eye Grabbing Dot For Fast Target Acquisition

Front sight: six, interchangeable, fiber optic rods offer a choice to match nearly all shooting and light conditions. The glowing, orange and green light pipes provide great contrast against dark target backgrounds.

Orders: 800-741-0015

SPECS: Steel, black, matte finish. .315" (8mm), .380" (9.7mm), .420" (10.7mm). Standard 3/8" dovetail. Light pipes: 1/16" (1.5mm), 3/32" (2.4mm), 1/8" (3.1mm), diameter. .720" (18m) long.

| #638-115-000 | .315" | Fiber Optic Sight, | 8C22G39 | \$ 27.99 |
|--------------|-------|--------------------|---------|----------|
| #638-000-013 | .380" | Fiber Optic Sight, | 8C23L19 | 28.99 |
| #638-000-014 | .420" | Fiber Optic Sight, | 8C23N19 | 28.99 |
| | | | | |

FRONT SIGHT ELEVATION CORRECTION CHART

How To Use Table Below - Suppose a rifle, having a sighting radius of 24" between front sight and receiver sight, shoots 6" high at 100 yards, even with the rear sight adjusted as low as possible. Remove front sight and measure overall height, preferably with a micrometer. This might be .410", such as a Marble No. 41N. Reference to columns for 24" and 6" on table below will show a necessary correction of .040". This would mean a new, higher front sight (with an overall height of .410" plus .040" for a corrected height of .450" such as a Marble No. 45N, should be installed.

Sighting in should be done with a benchrest or prone with a sand bag or other rest for the rifle. Do not put rifle barrel or forearm directly on solid surface, but put the back of your hand or wrist on the rest and hold forearm of the rifle securely in your hand with approximately the same tightness of grip you would use when shooting at running game. If the forearm or barrel is rested directly on the sand bag or rest, the rifle will shoot higher than when held firmly while shooting at game as more "muzzle flip" will occur.

AMOUNT OF ADJUSTMENT NECESSARY TO CORRECT ERROR Distance Between Front & Rear Sights

| | | 14" | 15" | 16" | 17" | 18" | 19" | 20" | 21" | 22" | 23" | 24" | 25" | 26" | 27" | 28" | 29" | 30" | 31" | 32" | 33" | 34" |
|-----------------------|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|-------|-------|-------|
| Amount | 1" | .0038 | .0041 | .0044 | .0047 | .0050 | .0053 | .0055 | .0058 | .0061 | .0064 | .0066 | .0069 | .0072 | .0074 | .0077 | .0080 | .0082 | .0085 | .0088 | .0091 | .0093 |
| of Error | 2" | .0078 | .0083 | .0089 | .0094 | .0100 | .0105 | .0111 | .0116 | .0122 | .0127 | .0133 | .0138 | .0144 | .0149 | .0155 | .0160 | .0156 | .0171 | .0177 | .0182 | .0188 |
| At | | .0117 | .0125 | .0133 | .0142 | .0150 | .0159 | .0167 | .0175 | .0184 | .0192 | .0201 | .0209 | .0217 | .0226 | .0234 | .0243 | .0251 | .0259 | .0268 | .0276 | .0285 |
| 100 Yards Given in | 4" | .0155 | .0167 | .0178 | .0189 | .0200 | .0211 | .0222 | .0234 | .0244 | .0255 | .0266 | .0278 | .0289 | .0300 | .0311 | .0322 | .0333 | .0344 | .0355 | .0366 | .0377 |
| Inches | 5" | .0194 | .0208 | .0222 | .0236 | .0250 | .0264 | .0278 | .0292 | .0306 | .0319 | .0333 | .0347 | .0361 | .0375 | .0389 | .0403 | .0417 | .0431 | .0445 | .0458 | .0472 |
| inches | 6" | .0233 | .0250 | .0267 | .0283 | .0300 | .0317 | .0333 | .0350 | .0367 | .0384 | .0400 | .0417 | .0434 | .0450 | .0467 | .0484 | .0500 | .05175 | .0534 | .0551 | .0567 |
| | | | | | | | | | | | | | | | | | | | | | | |

GALAZAN WINCHESTER M70/94 FRONT SIGHT HOOD

Front Blade Protection & Enhanced Sight Picture

pre-64 Model 70.

Protects the front sight from damage caused by normal field

use. Open front design allows plenty of light to reach the front blade

and provide an enhanced sight picture. Spring steel construction

for durability. Available for Model 94 carbine with sight ramp and

SPECS: Steel, blue, matte finish. 1" (2.5cm) long x 1/2" (12.7mm) wide.

#344-000-008 Pre-64 Model 70 Sight Hood, 4D7F49 ... 9.99

Model 94 - 1/2" high (12.7mm). Model 70 - 11/16" (16.7mm) high.

#344-000-007 Model 94 Carbine w/Ramp Sight Hood,

HIVIZ AK-47/74/AKM FIBER OPTIC FRONT SIGHT

Bright Fiber Optic For Easy Aiming

Replacement front sight post has a light-gathering fiber optic rod to produce a bright dot that's easy to acquire in a broad range of light conditions. Easily replaces the post on most AK-47, AK-74 and AKM rifle sights, no gunsmithing required.

Unique, U-shaped rod gathers far more light than a standard straight rod-perfect for low-light situations. Comes with two green and two red interchangeable rods that can be changed quickly using the included tool, so you can customize the sight picture or replace a damaged rod quickly. Elevation adjustable.

SPECS: Black steel post with 2 green and 2 red fiber optic rods. Includes detent

pin, sight wrench, fiber optic rod removal tool, carrying case, and instructions. #638-000-190 AK-47 FO Front Sight, 8C22F09 \$ 25.99

BROWNELLS MAUSER FRONT SIGHT BLANK

Ready To Fit & Shape For Custom Applications; Fits The Unique, Metric Dovetail

.375" high blade lets you zero the military Mausers, like the Model 96 Swede and 98, and other rifles with a metric dovetail, to point of aim. Square post blade gives an easy-to-see, well defined sight picture with the original, issue rear sights. Plenty of extra material so you

can file and shape the blade to original contour or a custom shape - and just the right height. 5.26mm dovetail fits the Mauser front sight base. Fits most Mauser 91 through 98 rifles with military sight base. SPECS: Steel, blued, matte finish, .077" (1.9mm) wide, .375" (9.5mm) high above 81° x .207" x .062" dovetail. May require minor fitting.

#078-050-000 Mauser Front Sight Blank, 8G11N99 ... \$ 15.99

MARBLE SPORTING REAR SIGHT **Traditional Sights Fit Many Brands**



Sporting Rear Sight Base with three styles of Uprights. Perfect as replacement sights for customizing the sight picture, or adding adjustment to fixed sight guns. Fits standard 3/8" dovetails; available with Flat Top, Semi-Buckhorn or Full Buckhorn Uprights.

SPECS: Dovetail Model - Total heights: #63 and 64, .275" (7.1mm) - .505" (12.4mm); #63H, 64H, 66H and 67H, .350" (9.0mm) - .630 (16.0mm); #65, 66, 67 and 68, .300" (7.6mm) -.510" (12.9mm).

| STOCK # | · · · · · · · · · · · · · · · · · · · | | PRI | CE | | | | | | | |
|----------------------|---------------------------------------|-------------|----------|---------|----------|--|--|--|--|--|--|
| | FL | AT TOP SI | GHTS | | | | | | | | |
| #579-063-001 | Dovetail | Short | 63 | 9G18D39 | \$ 22.99 | | | | | | |
| #579-063-003 | Dovetail | Short | 63H | 9G17K59 | \$ 21.99 | | | | | | |
| #579-066-001 | Dovetail | Long | 66 | 9G18A39 | \$ 22.99 | | | | | | |
| #579-066-003 | Dovetail | Long | 66H | 9G17B59 | \$ 21.99 | | | | | | |
| SEMI-BUCKHORN SIGHTS | | | | | | | | | | | |
| #579-064-001 | Dovetail | Short | 64 | 9G18E39 | \$ 22.99 | | | | | | |
| #579-067-001 | Dovetail | Long | 67 | 9G20F79 | \$ 25.99 | | | | | | |
| #579-067-003 | Dovetail | Long | 67H | 9G17M59 | \$ 21.99 | | | | | | |
| | FULL- | BUCKHOR | N SIGHTS | | | | | | | | |
| #579-065-001 | Dovetail | Short | 65 | 9G18M39 | \$ 22.99 | | | | | | |
| #579-068-001 | Dovetail | Long | 68 | 9G18P39 | \$ 22.99 | | | | | | |
| - Advise # - | Flat Top F | Rear, 9G18E | 0.39 | | \$ 22.99 | | | | | | |
| - Advise # - | | khorn Rea | | | 22.99 | | | | | | |
| — Advise # — | | horn Rear, | - | | 22.99 | | | | | | |

MARBLE FOLDING LEAF REAR SIGHT

Perfect "Back-Ups" For Scoped Guns

Folds down when not in use. Strong spring secures sight in "up" or "down" position. The reversible notch piece gives choice of "U" or "V" notch. Styles and heights available to fit most standard rear sight dovetails. The chart shows the overall sight height for those sights below

69 & 69W - Height, .370" (9.4mm) to .480" (12.2mm)

69H & 69WH - Height, .470" (11.9mm) to .600" (15.2mm).

69WEH - Height, .520" (13.2mm) to .640" (16.3mm)

No. 69H is .096" (2.4mm) higher than standard folding leaf. Blade & Screw replacement parts available to maintain your existing, foldingleaf sights.



FLAT TOP FOLDING LEAF SIGHT WITH WINDAGE

NO.69W - "W" indicates Windage and can be used wherever No. 69 sights are indicated in Marble sight chart.

NO.69WH - "H" indicates "high" and can be used wherever No.

69H is indicated. "H" is .096" (2.4mm) higher. No.69WEH - "EH" indicates "extra high" and is elevation adjustable .538" to .657".

| #579-069-002 | No. 69W Marble's Flat Top, Windage, 9G19P19 | \$ 23.99 |
|--------------|--|----------|
| #579-069-003 | No. 69WH Marble's Flat Top, Windage, 9G19F99 | 24.99 |
| #579-000-072 | No. 69WEH Marble's Flat Top, Windage, 9G19I19 | 23.99 |



order on the web brownells.com

MARBLE DOVETAIL FRONT RAMP



Graceful & Attractive For Rifles & Muzzleloaders

Solid steel ramps for custom fitting fiber optic, ivory and brass bead sight blades. Available in two heights and four barrel contours to fit a wide selection of current and older production rifles. Ramp attaches to barrel with a single screw under the sight body and solder; flat base is drilled for two mounting screws.

SPECS: Steel, blue, polished finish. .340* (8.6mm) wide. 2" (5cm) long. Height is from the top of barrel to the bottom of dovetail.

| STOCK # | BL DIA. | HGT | STOCK # | BL DIA. | HGT |
|--------------|---------|-------|--------------|---------|-------|
| #579-000-034 | .625 | .100" | #579-000-038 | .625 | .225" |
| #579-000-035 | .6875 | .100" | #579-000-039 | .6875 | .225" |
| #579-000-036 | .875 | .100" | | | |
| | | .200 | #5/9-000-039 | .68/5 | .225 |

Advise # — Dovetail Front Ramp, 9G10K39 \$ 12.99

MARBLE UNI-RAMP FRONT SIGHT



Solid Steel Body For Strength; Long Rod Picks Up Lots Of Light

Glowing 3/4"-long fiber optic rod gives excellent visibility. Quickly replaces screw-held front sights on rifles, shotguns and muzzleload-

ers. Two blade heights available. SPECS: Steel, blue, polished finish. 2" (5cm) long. Height - .405" (10.3mm) or .470" (11.9mm). Fits \$/\$" O.D. barrel contour. Optic rod \$/\$" (19mm) long,

| STOCK # | HEIGHT | CONTOUR | PRICE |
|--------------|--------|---------|-------------------------|
| #579-000-016 | .405" | 5/8" | 9G15Q99 \$ 19.99 |
| #579-000-017 | .470" | 5/8" | 9G15F99 \$ 19.99 |

MARBLE CONTOUR FRONT SIGHT

The Standard In The Industry

Precision-made sights for rifles, both with and without ramp bases. The blade is gracefullly contoured, sloping toward the front. Made of steel and nicely blued to look good on any gun. RAMP MOUNTED FRONT SIGHT:

SPECS: Steel, blue, polished finish. .620" (15mm) long.







"MR" features a straight-sided base for guns having a ramp base on the barrel. All "MR" sights have a .340" (8.6mm) wide base. The BARREL MOUNTED FRONT SIGHT has rounded base sides for guns with the front sight dovetail cut directly into the barrel. "W" sights have a .¹⁷/₁₂" (13.5mm) wide base. Ramped and Barrel front sights are available with three beads, Pope's Island Gold, flat faced gold available in ¹/₁₆" (1.6mm) or ¹/₁₂" (2.4mm) diameter. Ivory, flat faced white polymer in ¹/₁₆" (1.6mm) or ¹/₁₂" (2.4mm) diameter. GLOW SIGHTS: Two colors - Orange or Green .060" dia. optic rod. RAMP MOUNTED - .340 wide base. BARREL MOUNTED - ¹/₁₂" wide base. Barrel wide base.

| - Advise # - | White or Gold Sight, 9G11B99 | \$ 14.99 |
|------------------------------|------------------------------|----------|
| Advise # — | Glow Sight, 9G15K19 | 18.99 |

| | | RAMP MOUNTED F | RONT SIGHTS | GLOW SIGHTS | |
|------|-------|-----------------|-----------------|--------------|--------------|
| HGT | MRBL# | STK# 1/16" GOLD | STK# 3/32" GOLD | STK# GREEN | STK# ORANGE |
| .260 | 26-MR | #579-502-621 | NA | NA | NA |
| .290 | 29-MR | #579-502-921 | NA | NA | NA |
| .312 | 31-MR | #579-503-121 | NA | #579-603-126 | #579-603-125 |
| .343 | 34-MR | #579-503-421 | #579-603-421 | #579-603-426 | #579-603-425 |
| .375 | 37-MR | #579-503-721 | #579-603-721 | #579-603-726 | #579-603-725 |
| .410 | 41-MR | #579-504-121 | #579-604-121 | #579-604-126 | #579-604-125 |
| .450 | 45-MR | #579-504-521 | NA | #579-604-526 | #579-604-525 |
| .500 | 50-MR | #579-505-021 | NA | NA | #579-605-025 |


| | | BARREL MOUN | TED FRONT SIGHT | S | | GLOW SIGH | TS |
|------|-------|-----------------|------------------|-----------------|------------------|--------------|--------------|
| HGT | MRBL# | STK# 1/16" GOLD | STK# 1/16" IVORY | STK# 3/32" GOLD | STK# 3/32" IVORY | STK# GREEN | STK# ORANGE |
| .343 | 34-W | #579-103-431 | #579-103-432 | #579-203-431 | NA | NA | NA |
| .375 | 37-W | #579-103-731 | #579-103-732 | #579-203-731 | #579-203-732 | #579-203-736 | #579-203-735 |
| .410 | 41-W | #579-104-131 | NA | #579-204-131 | #579-204-132 | #579-204-136 | #579-204-135 |
| .450 | 45-W | #579-104-531 | #579-104-532 | #579-204-531 | #579-204-532 | #579-204-536 | #579-204-535 |
| .500 | 50-W | #579-105-031 | #579-105-032 | #579-205-031 | #579-205-032 | #579-205-036 | #579-205-035 |
| .538 | 53-W | #579-105-331 | NA | #579-205-331 | NA | NA | NA |
| .570 | 57-W | #579-105-731 | #579-105-732 | #579-205-731 | NA | NA | NA |
| .312 | 31-W | NA | NA | #579-203-131 | NA | NA | NA |

| | MARBLE Chart To Determine Overall Sight/Ramp Heights | | | | | | | | | | | | | |
|--------------|--|-----------------|--------------|-------------------|-----------------|--------------|-------------------|-----------------|--------------|-------|-----------------|--------------|-------------------|-----------------|
| Sight No. | Ramp | Total Height | Sight No. | Ramp | Total Height | Sight No. | Ramp | Total Height | Sight No. | Ramp | Total Height | Sight No. | Ramp | Total Height |
| 26MR | 3/16" | .3545 | 26MR | 3/8" | .5420 | 41MR | 5/16" | .6295 | 37MR | 7/16" | .7195 | 34MR | 9/16" | .8125 |
| 29MR | 3/16" | .3845 | 45MR | ³ /16" | .5445 | 53MR | ³ /16" | .6325 | 26MR | 9/16" | .7295 | 53MR | 3/8" | .8200 |
| 31MR | 3/16" | .4065 | 34MR | 5/16" | .5625 | 29MR | 7/16" | .6345 | 45MR | 3/8" | .7320 | 50MR | 7/16" | .8445 |
| 34MR | ³⁄ ₁₆ " | .4375 | 29MR | 3/8" | .5720 | 31MR | 7/16" | .6565 | 41MR | 7/16" | .7545 | 37MR | 9/16" | .8445 |
| 37MR | ³ /16" | .4695 | 31MR | 3/8" | .5940 | 37MR | 3/8" | .6570 | 53MR | 5/16" | .7575 | 41MR | 9/16" | .8795 |
| 26MR | 5/16" | .4795 | 50MR | ³ /16" | .5945 | 45MR | 5/16" | .6695 | 29MR | 9/16" | .7595 | 53MR | ⁷ /16" | .8825 |
| 41MR | ³ ⁄16" | .5045 | 37MR | 5/16" | .5945 | 34MR | 7/16" | .6875 | 31MR | 9/16" | .7815 | 45MR | ⁹ ⁄16" | .9195 |
| 29MR | 5/16" | .5095 | 26MR | ⁷ /16" | .6045 | 41MR | 3/8" | .6920 | 50MR | 3/8" | .7320 | 50MR | 9/16" | .9695 |
| 31MR | 5/16" | .5315 | 34MR | 3/8" | .6250 | 50MR | 5/16" | .7195 | 45MR | 7/16" | .7945 | | | |

| | ECTIO | | | LEADREAD | EDON |
|---|------------------------|-----------------|-----------------|----------------|--------------|
| MARBLE | | SPORTING REAR | | LEAF REAR | FRON |
| VINCHESTER RIFLES 892 Rep25-20, .32-20, .38-40, .44-40 | FLAT TOP 66 | SEMI-BUCK 67 | FULL BUCK 68 | FLAT 69 | NO. 31W |
| 1892 Carb25-20, .32-20, .38-40, .44-40 | 63 | 64 | 65 | 69 | - |
| 392 Carb. with ramp | 63 | 64 | 65 | 69 | - |
| 394 Rep32-40, .38-55 | 66 | 67 | 68 | 69 | 31W |
| 394 Rep25-35, .30-30, .32 Spec. | 66 | 67 | 68 | 69 | 45W |
| 1894 with ramp .25-3530-30, .32 Spec. | 66 | 67 | 68 | 69 | - |
| 894 Carb32-40, .38-55 | 63 | 64 | 65 | 69 | - |
| 394 Carb25-35, .30-30, .32 Spec. | 63 | 64 | 65 | 69 | 894 |
| 394 Carb. with ramp | 63 | 64 | 65 | 69 | - |
| lod. 61 Pump Action .22 Cal. | 63 | 64 | 65 | 69 | 34W |
| od. 62 Rep. Rifle .22 Cal. | 63 | 64 | 65 | 69 | 34W |
| lod. 63 .22 L. R. Auto | 63 | 64 | 65 | 69 | 34W |
| lod. 64 .25-35, .30-30, .32 Spec. lod. 65 .25-20, 32 | 66 | 67 67 | 68 | 69 | |
| lod. 65 .25-20, 32 lod. 67 Single Shot .22 Cal. | 63 | 64 | 68 65 | 69 69 | 34W |
| lod. 68 .22 Cal. | 63 | 64 | 65 | 69 | 45W |
| lod. 69 .22 Cal. | 63 | 64 | 65 | 69 | 45W |
| lod. 70 All Cal. | 66 | 67 | 68 | 69 | - |
| lod. 71 .348 Cal. | 66 | 67 | 68 | 69 | - |
| lod. 77 .22 Cal. S. L. Rifle | 63 | 64 | 65 | 69 | 41M |
| lod. 88 .308 Cal. L. A. Rifle | 66 | 67 | 68 | 69 | - |
| lod. 100 | 63H | 64H | 65 | 69H | 26MR |
| IARLIN RIFLES | - | | | | |
| lod. 39, A Rep. Rifles | 63 | 64 | 65 | 69 | 37M |
| od. 39 A with Ramp | 63 | 64 | 65 | 69 | - |
| lod. 56 22 Cal. L. A. | 63 | 64 | 65 | 69 | - |
| lod. 36, 336 rifle and carbines | 66 | 67 | 68 | 69H | 45W |
| od. 336, SC .35 Cal. | 66 | 67 | 68 | 69H | 37M |
| EMINGTON RIFLES | | | | | |
| lod. 12 Rep. Rifle .22 Cal | 63 | 64 | 65 | 69 | 31W |
| lod. 121 Fieldmaster .22 Cal. | 63 | 64 | 65 | 69 | 37M |
| od. 121 Fieldmaster (1936 Series) .22 Cal. | 63M | 64M | - | - | 37M |
| od. 141 Gamemaster .30, .32, .35 | 66H | 64 | 65 | 69 | 31M |
| lod. 241 Speedmaster .22 Auto-Ldg. | 63M | 64 | 65 | 69 | 37W |
| lod. 33, 34, 41, .22 Cal. Single Shot | 63 | 64 | 65 | 69 | 31W |
| lod. 341 Speedmaster .22 Cal. lod. 510. 513T | 63 63 | 67H | - | 68H | 31W |
| | 63 | 64 | 65 65 | 69 69 | 37M 37M |
| lod. 511, 512, 550, 552 | | | | | |
| lod. 514 lod. 521T .22 Cal | 63M 63 | 64 64 | 65 65 | 69 69 | 37M 45W |
| lod. 5211 .22 Cal. | 63M | 64M | - | 69 | 37M |
| lod. 700 | 63 | 64 | - | 69 | 41MR |
| lod. 700 lod. 721, 722 All Cal. | 63H | 64H | - | 69H | 34W |
| lod. 760 All Cal. | 66 | 67 | 68 | 69H | 3444 |
| lod. 740 At Cat. | 63H | 64H | - | 69H | 37M |
| od. 740 ADL | 63H | 64H | _ | 69H | 3/14 |
| od. 742 | 63H | 64H | 65 | 69 | 41 |
| lod. 760 .22 Cal. | 66H | 67H | 65 | 69 | 41 |
| od. 725 | 66 | 67 | - | 69 | 31M |
| On late Model 700, 721, 722, 725, 74 | 0, 760 No. 25 R | lamp | | | |
| Sight Base is required to use Marble Oper | ricear signts (no | n stocked) | | | |
| AVAGE RIFLES lod. 340, .30-30 Cal. for Gun with Slot in Ramp | 63H | 64H | | 69H | - |
| od. 342 .22 Hornet | 63H | 64H | - | 69H | - |
| od. 1899 E. F. G. | 66 | 67 | 68 | 69 | - |
| od. 99R .250 and .300 Cal. | 66 | 67 | 68 | 69 | - |
| /pes A, B, C, D & H. Serial No. below 297,000 in Cal22 HP25-35, .30-30, .303300 | | - | | 69H | 45W |
| or Featherweight | | _ | _ | _ | |
| od. 99T .30-30 & .303 Cal. | 63 | 64 | 65 | 69H | - |
| 9F, G & EG .22 Cal. HP; 99RS .250 | 63 | 64 | 65 | 69H | 34W |
| 9F, G & K .30-30 & .303; Carbines .250, .30-30, .303 | 66 | 67 | 68 | 69H | 37M |
| 9T .22 HP, .250, .300, 99A, E. F. G. EG.K & R .250, 99G, K, RS .300 | 66 | 67 | 68 | 69H | 45W |
| lod. 110MC-MCL | 66H | 67H | - | 69H | 201/2 |
| od. 99DL .300 Sav. od. 99E .243, .300 Sav. and .308 | 66 66 | 67 67 | 68 68 | 69H 69H | 26MF 29MF |
| | 00 | 0/ | <u> </u> | USH | ZAMP |
| TEVENS RIFLES Iod. 87 | 63H | 67H | 68 | 69H | 37W |
| lod. 87K | 63H | 64H | 65 | 69H | 37W |
| ROWNING | | | | | |
| 2 Automatic late models 2 Automatic | 63 | 64 | - 65 | - 69 | 37M - |
| Add30, .06 | - | - | - | - | |
| TURM-RUGER RIFLES | | | | | |
| lod. 44 Mag. | - | - | - | 69H | 45MF |
| | | | | | |
| od. 10/22 No sight available. | | - | | 69 | 41MR |

CALCULATING SIGHT HEIGHTS

Determining proper sight height is not difficult. Just remember the front and rear sights must be the same height above the center of the barrel. And, when you make your measurements, you MUST use a caliper or micrometer. A few thousandths can have a substantial effect, and this is no place for a tape measure or eyeballing!





- sight. Barrel outside diameter divided by 2.
- **C** = Distance from centerline to top of barrel at front **D** = Front sight height. sight. Barrel outside diameter divided by 2.

DETERMINING FRONT SIGHT HEIGHT

When you have a rear sight and need to find the correct front sight height, the formula is (A + B) - C = D. With the rear sight in place:

- 1) Measure barrel diameter at the location of the rear sight and divide by 2 to get Dimension A.
- 2) If the rear sight is adjustable, set the blade in the MIDDLE of its travel. Then measure the total rear sight height from the top of the barrel, to the top of the sight blade to get Dimension B. For example, on a WGOS with a 1/4" blade, the mid-setting is .462" high, so Dimension B would be .462".
- 3) Measure the barrel diameter at the projected location of the front sight and divide by 2 to get Dimen-
- 4) Add Dimension A + Dimension B, then subtract Dimension C from the total to get Dimension D, the required height of the front sight above the top of the barrel.
- 5) Choose the tallest ramp and shortest sight blade combination that's closest to the results in Step 4. In the example below, the required front sight height is .587". A Williams 3/8" (.282" high) ramp and a Marble #31MR sight (.312" high) will provide a combined height of .594". Or combine a Williams .250" high

blade with a Williams 7/16" (.3445") ramp for a total height of .5945".

DETERMINING REAR SIGHT HEIGHT

When you have a front sight and need to find the correct rear sight height, the formula is (C + D) - A = B. With the front sight in place:

- 1) Measure barrel diameter at the projected rear sight location and divide by 2 to get Dimension A.
- 2) Measure the barrel diameter at the location of the front sight and divide by 2 to get Dimension C.
- 3) Measure the front sight height from the top of the barrel to the top of the sight blade to get Dimension D.
- 4) Add Dimension C + Dimension D, then subtract Dimension A from the total to get Dimension D, the required height of the rear sight above the top of
- 5) Choose a rear base and sight combination with a total height closest to D. If the rear sight is adjustable, the total height should match Dimension D when the sight is positioned in the MIDDLE of the adjustment area.

EXAMPLE WITH NUMBERS D = .587" B = .462"A = .475'C = .350" .700" .950'

| FRONT SIGHT CALCULATION: | REAR SIGHT CALCULATION: |
|--------------------------|-------------------------|
| (A + B) - C = D | (C + D) - A = B |
| (.475 + .462)350 = .587 | (.350 + .587)475 = .462 |
| .937350 = .587" | .937475 = .462" |

MARBLE BULLSEYE REAR SIGHT



For Fast Target Acquisition & Improved Accuracy

Barrel-mounted, dovetail Bullseye sight gets you on target fast with perfect alignment for improved accuracy. Steel, double-ring peep design ensures consistent sight alignment and helps improve shooting form. The moment the rear sight is misaligned, the front sight drifts out of the center ring, telling the shooter to re-align. Replaces standard 3/8" dovetail rear sights on many rifles. For use with bead-type or traditional blade front sights. Adjustable models are available with a short or long base and six-position step elevator that's adjustable in .030" increments for precise elevation settings. Fixed model features the same Bullseye peep design but without the extended base and is not elevation adjustable. All models are drift adjustable for windage. May require minor fitting.

SPECS: Steel, blue, polished finish. Fits nominal 3/8" (9.5mm) dovetail. Outside Ring O.D. - 9/16" (1.4cm). Inside Ring I.D. - .15" (3.8mm). Adjustable -.338"-.535" (8.6mm - 13.5mm) elevation adjustment in six, .030" (.76mm) increments. OAL from rear of dovetail - Long: 21/2" (6.3cm). Short - 11/2" (3.8cm). Fixed - .438 (11.1mm) fixed height from bottom of dovetail to center of inside ring. 7/16" (1.1mm) long.

| #579-000-163 | Short Adj. Bullseye Sight, 9G18G3 | 9 \$ 22.99 |
|--------------|-----------------------------------|--------------|
| #579-000-164 | Long Adj. Bullseye Sight, 9G17D59 | 21.99 |
| #579-000-165 | Fixed Bullseye Sight, 9G17K59 | 21.99 |

MARBLE #95 FOLDING SPORTING **REAR SIGHT**

Traditional Appearance: Folds Down For Storage Or Carry



SPECS: Steel, blue, polished finish. Leaf - .300" (7.8mm) high, .630' (15.8mm) wide. Fits nominal 3/8" (9.5mm) dovetail

#579-000-082 #95 Folding Rear Sight, 9G24Q79..... \$ 30.99

SIGHT APERTURES

A Complete Selection Of Williams Apertures

Have the right combination of aperture and disc always on hand. Perfect to change between hunting and target shooting or as replacements for missing ones. Fit Williams and Lyman, 7/32"-



STANDARD SHANK SIGHT APERTURES - Standard lengthshank fits Williams Foolproof, Target Foolproof, and 5D only.


SPECS: 7/32"-40 thread. 3/8" or 1/2" STD Aperture Paks include three, 3/8" or ½" O.D. apertures: one each with .050", .093" and .125" aperture holes. 7/8" x .050" Target Aperture Pak includes three, 7/8" O.D. apertures with 050" aperture holes


| #080-766-380 | 3/8" Std. Aperture Pak, | 8K00QLJ | \$ 59.99 |
|---------------------|--------------------------|---------|----------|
| #080-766-500 | 1/2" Std. Aperture Pak, | 8K00NGJ | 36.99 |
| #080-766-705 | 7/8" x .050" Tgt. Apts., | 8K00KBA | 46.99 |

INDIVIDUAL STANDARD APERTURES - One Per Package SPECS: 7/32"-40 thread, 3/8", 1/2" or 7/8" O.D apertures.

| #080-766-381 | 3/8" x .050" Aperture, | 8K00CRI | \$ 22.99 |
|--------------|------------------------|---------|----------|
| #080-766-382 | 3/8" x .093" Aperture, | 8K00DXN | 23.99 |
| #080-766-383 | 3/8" x .125" Aperture, | 8K00EWP | 22.99 |
| #080-766-501 | 1/2" x .050" Aperture, | 8K00NGD | 17.99 |
| #080-766-502 | 1/2" x .093" Aperture, | 8K00EKR | 17.99 |
| #080-766-706 | 7/8" x .050" Aperture, | 8K00QSF | 16.99 |

LONG SHANK SIGHT APERTURES - Fits Williams WGRS ONLY. Longer shanks allow correction for proper eye relief. Standard or brass-ringed, Twilight (TW) aperture. SPECS: 7/32"-40 thread. 3/8" Long Shank (L/S) or 3/8" Twi-





TWILIGHT APERTURES - A light gathering brass ring surrounds the peep to enhance visibility in low light. Fits Foolproof, Target Foolproof, and 5D sights only.

SPECS: 7/32"-40 thread. Standard length shank. 3/8" Twilight (TW) Aperture Pak includes three 3/8" O.D. apertures: one each with .050", .093" and .125"

| aperture notes. Il | naiviauai aperiures aiso si | ola separately. |
|--------------------|-----------------------------|-----------------|
| #080-767-380 | 3/8" TW Aperture Pak, | 8KO0FDS\$ 47.99 |

| #080-767-050 | 3/8" x .050" TW Aperture, | 8К00GCG | \$ 17.99 |
|--------------|---------------------------|---------|----------|
| #080-767-093 | 3/8" x .093" TW Aperture, | 8K00LDL | 17.99 |
| #080-767-125 | 3/8" x .125" TW Aperture, | 8K00CIC | 17.99 |

INDIVIDUAL TWILIGHT APERTURES - One Per Package

KENSIGHT M1 CARBINE **REAR APERTURE SIGHT**



High Quality Reproduction Of The Factory Original

Modern, high-quality reproduction of the original rear sight makes restoring your M1 carbine easier and the final job look authentic. Patterned

after the factory rear sight using modern CAD/CAM design techniques and wire EDM cut from 4140 bar stock for tight tolerances. Features audible clicks for precise windage adjustment and preset range increments for elevation adjustment. SPECS: Steel, blued, matte finish. Fits M1 Carbine.

#100-004-084 Rear Aperature Sight, 5A25J66...... \$ 29.99

N.E.C.G PEEP-SIGHT



Provides Excellent Sight Picture, Clamps To Weaver-Style Bases

Solid-steel sight is fully adjustable for windage and elevation; provides a primary sight when hunting dangerous game and a scope is not practical, or an emergency

backup. Furnished with .093" and .125" diameter apertures; allows you to shoot very accurately, even under poor light conditions. Fits Weaver-style or Picatinny base, may be easily removed and returned to zero every time. Includes two elevation slides.

SPECS: Steel, blue finish. 1¹/₈" (2.9cm) long, 1¹/₂" (3.8cm) wide, 1" (2.5cm) high. Aperture - 7/32-40 thread, accepts Williams and Merit sight discs.

#661-000-035 Weaver Peep Sight, 1F83J29 \$ 97.99

order on the web

brownells.com

LYMAN TARGET FRONT SIGHT



Low, All Steel With Eight Inserts

All steel front sight with eight interchangeable sight inserts that are locked into place by threaded cap. Sight includes insert set. SPECS: Sight tube- 9/16" (14.3mm) dia.. Dovetail base is 3/8" (9.5mm) wide for standard dovetail.

Use 17AML with 57SML Receiver sight. 17 ATC is for use with factory vernier tang sight on T/C muzzleloaders. 17AEU fits European 9mm (nominal .360" x .070") dovetail. HEIGHT is from bottom of dovetail to center of aperture.

| STOCK # | HEIGHT | MODEL |
|--------------|--------|-------|
| #539-017-360 | .404" | 17AHB |
| #539-017-444 | .465" | 17AEU |
| #539-017-445 | .494" | 17AMI |
| #539-017-446 | .494" | 17AML |
| #539-017-532 | .584" | 17AUG |
| #539-017-852 | .854" | 17ATC |
| | | |

— Advise # — 17A Front Sight, 5K35L99 \$ 39.99

20 MJT GLOBE FRONT SIGHT - Machined steel. globe front with interchangeable inserts. SPECS: Steel, blued. 1¹/₄" (3.1cm) long, .875" (22.2mm diameter. 3/8" (nominal) dovetail, 1.8 oz. (51a) wt. .700" (17mm) from bottom of dovetail to center of aperture. Includes 2 posts, 5 aper-

#539-620-000 MJT Globe Sight, 5K48D99 \$ 57.99

LYMAN RECEIVER SIGHT

Three Styles That Fit a Variety of Gun Models

Rugged and precise sights, machined to hug the receiver for lowest line of sight, least protrusion. Audible-click, 1/4 minute adjustments for elevation and windage. Elevation slide is scribed in 3 minute increments. Quick release allows

slide to be removed with a press of a button. Elevation stop screw permits instantaneous return to zero. Model 57

is for round receivers; Model 66 is for flat receivers, 66 WB includes semi-target knobs. The 57 SMET includes target knobs. SPECS: Aluminum, black, anodized. Comes with two apertures, 1/2" (12.7mm) x .093" (2.3mm) and 5/8" (15.8mm) x .040" (1.1mm).

| STOCK # | MODEL | FITS | |
|--------------|---------|--------------------------------------|--|
| #539-066-002 | 66 LA | MARLIN 336 | |
| #539-000-001 | 57 GPR | MUZZLELOADERS Lyman Great | |
| | | Plains, Trade, Deer Stalker | |
| #539-057-007 | 57 SMET | IN-LINE MUZZLELOADERS White | |
| | | Systems In-line | |
| #539-066-001 | 66A | REMINGTON 141 | |
| #539-066-001 | 66 A | WINCHESTER 64, 92, 94 | |
| #539-000-004 | 66 WB | WINCHESTER 1886 Win. & Browning | |
| #539-057-007 | 57 SMET | MAUSER 98, 91, 93, 94, 95, 96, 1904, | |
| | | 1909, 1936, G33/40 | |
| #539-057-007 | 57 SMET | SPRINGFIELD 1903 | |

TRUGLO DOVETAIL FRONT SIGHT



Metal Body For Durability; Bright Fiber Optic Insert Increases Visibility

Light-gathering red fiber optic rod offers a bright, eye-grabbing bead for fast sighting. Fits nominal 3/8" dovetail.

SPECS: Aluminum, black, anodized finish. 3/4" (19mm) long. Red optic rod is 3/4" long, .060" (1.5mm) diameter. Height measured from top of ramp to top of sight.

#902-000-008 F/O Dovetail Front Sight, .450" High, 2K16K14.....\$18.99

N.E.C.G. RUGER® RECEIVER SIGHT



Clamps Quickly To Ruger® Integral Bases

Finely machined steel receiver sight clamps to factory ring notches on Ruger rifles; serves as a primary hunting sight in situations where a scope may not be practical. Pack as

an emergency sight to save your hunt in case of scope failure. Install and remove without loss of zero. Height matches most M-77°. 77/22° and No. 1 factory front sights. Includes .093" and .125" apertures that draw your eye to the sight for fast sight alignment. Adjustable for windage and elevation.

SPECS: Steel, blue finish. 11/4" (3.2cm) long. 3/4" (19mm) high. 11/4" (3.2cm) wide. #661-040-100 Receiver Sight, for Ruger, 1F82A44 \$ 96.99

N.E.C.G RIMFIRE RECEIVER SIGHT

Precision Target Acquisition; Mounts On Grooved Rimfire Receivers

Machined, steel peep sight gives you a precise sight picture for pin-point accuracy from your match or hunting rifle. Sight attaches to grooved, 3/8" dovetail, rimfire receivers. Fully adjustable for windage and el-

evation; comes with .093" and .125" apertures, plus a handy wrench for easy installation. SPECS: Steel, black, matte finish. 1" (2.5cm) long, 3/4" (19mm) wide, 1/2"

(12.7mm) high. .093" (2.3mm) and .125" (3.1mm) apertures. Fits grooved, 3/8" (9.5mm) rimfire receivers.

#661-000-044 Rimfire Receiver Sight, 1F87F54..... \$ 102.99

SAMSON MFG. RUGER® 10/22® **B-TM SIGHT SET**



Iron Sight Upgrade Enables a More Comfortable "Head-Up" Stance Plus Rail Section for Mounting a Red Dot

Got a Samson B-TM folding stock on your 10/22°? Congratulations! It's a great upgrade to an already great rimfire rifle. But.... some folks would really like a higher sight picture so they can maintain a more comfortable cheekweld on the B-TM. If you're one of these folks - or if you just want to get better "iron" sights and/or mount a red dot on your 10/22° - Samson's B-TM Sight set is a must-have. Compared to the 0.7" height over bore of 10/22° fac'tree iron sights, Samson's elevated sights have a 1.25" height over bore that allow for a much more comfortable and natural "head up" cheekweld. Rear sight mounts to the factory drilled-and-tapped scope mount holes in the receiver. Samson's rear aperture is adjustable for windage, and your final setting, not to mention the peep itself, is guarded by a sturdy set of protective shoulders. Even better, the rear sight assembly includes a machined 6" Picatinny rail section that lets you mount a red dot optic to co-witness with the iron sights. The front sight post is fully adjustable for elevation, while a pair of "ears" flanking the post protect it from bumps, dings, and unintended impact with stuff. It mounts to the factory front sight dovetail, so a dovetailed barrel IS required for installation; will not fit rifles without factory iron sights. By the way, the front and rear sights are designed to mimic the look of the Mini-14® factory iron sights. Front and rear sight assemblies are machined aluminum with a tough matte black hardcoat anodized finish. Package includes sight adjustment tool, mounting hardware, and 5/64" hex wrench.

#100-047-442 B-TM Sight Set for 10/22°, 5K80B99 . . . \$85.45

SMITH ENTERPRISE M1/M14/M1A FRONT & REAR SIGHTS





For Easy Restorations Or Competition

Heat-treated. chrome moly front and rear sights make it fast and easy to upgrade your original military sights for improved strength and accuracy.

Parkerized finish reduces glare and helps deflect light for a clear, easy-to-acquire sight picture in all light conditions. Match-type front sights feature a narrow, .062" wide front blade for a crisp, clean sight picture at all normal competition ranges.

SPECS: Steel, Parkerized finish. . 062" (1.6mm) wide blade. Includes setscew

#851-100-101 Match M1 Garand Front Sight, 1E44F09.. \$ 48.99 #851-114-106 Match M14/M1A Front Sight, 1E37D39 . . 43.99

TRUGLO RIFLE SIGHT SET



Fully Adjustable, Fiber **Optic Increases Visibility**

Combination red front and green rear provides eye-catching contrast for guick sight alignment. Fiber optic rods gather available light and draw your eye to

the sights to get you on target fast. Machined aluminum body adiusts for windage and elevation. Front and rear set replaces factory sight without alteration or gunsmithing. Ruger® 10/22® fits factory barrels. Winchester 94 fits models with a front sight ramp. SPECS: Aluminum, black, matte finish. Front and rear set.

#902-000-006 Ruger 10/22 Rifle Sight Set, 2K33G14.. \$ 38.99 #902-000-007 Winchester 94 Rifle Sight Set, 2K33K14 . . 38.99

TECH SIGHTS RUGER 10/22 GI-STYLE APERTURE SIGHTS

Provides Familiar M16 Service Rifle Sight Picture & Improved Accuracy





#100-006-910 TSR100 10/22 Sight Set, 2C62E89 \$ 73.99 #100-006-911 TSR200 10/22 Sight Set, 2C70K54..... 82.99

TRIJICON® RIFLE SIGHT

Self-Luminous Replacement Sights For Popular Rifles

The ultimate, self-luminous rifle sight. Improves sight pickup and visibility during low-light hours when game is most active. All sights include rugged sapphire crystal, self-il-



luminating Tritium lamps for a bright, well-defined aiming point and extra-long life. Lamps guaranteed by the manufacturer to remain self-luminous for 12 years.

SPECS: Steel body, blued. Tritium insert. Includes front and rear sight unless shown in chart. All sights are adjustable if rifle or shotgun barrel was originally equipped with factory adjustable sights.

| STOCK # | FITS | PRICE | |
|--------------|--------------------------------|------------------|--|
| #892-415-125 | AR-15 A1/A2 front only | 2H00LJS \$ 49.99 | |
| #892-415-025 | AR-15 A1/A2 with 10-36 windage | 2H00GBG \$ 68.99 | |
| | screws | | |
| | | | |

#892-407-001 Remington 74, 76, 760, 7400, 7600, 2H00LEB \$ 99.99 870, 1100, 11-87 (w/rifle sights) front and rear 3-dot

WILLIAMS BRASS BEAD RIFLE FRONT SIGHT

SHAVER GLOBE SIGHT INSERTS Finer Crosshairs, Posts Or Silhouettes For **Greater Accuracy** Developed specifically for silhouette shooters

using globe front sights. Thinner, more versatile crosshairs, posts and apertures do away with thick, bulky inserts; won't hide that 500 meter

ram or tiny "black" you need to hit. SPECS: 1095 spring steel, blued. .01" (.25mm) thick. Post & Aperture Card includes 3 apertures, 4 crosshairs, 3 posts. Lyman 17A also fits Browning BPCR. 470" (12mm) dia. Redfield/Alley - .550" (14mm) dia. Fits Redfield 65/66 and Alley globe sights. Large Lyman/Anschutz - .675" (17.1mm) dia.

| STOCK # | MODEL | PRICE | |
|--------------|----------------------|-------------------------|--|
| #781-100-017 | Lyman 17A Sight | 1H32Q79 \$ 40.99 | |
| #781-100-010 | Redfield/Alley | 1H28Q89 \$ 33.99 | |
| #781-100-011 | Large Lyman/Anschutz | 1H27P99 \$ 34.99 | |

All-Metal Beads for Ramps & **Dovetailed Barrels**



Thin, streamlined, almost invisible blade with a machined bead gives a crisp, highly visible sight picture. SPECS: Steel blade, blued, Brass bead, polished. Nominal .375" dovetail. Narrow

are .250" (6.35mm) wide to fit Williams Streamlined and Shorty Ramps. Medium are .340" (8.6mm) wide to fit factory ramps including Marlin and Remington. Wide are .531" (13.5mm) for dovetailed barrels on .22 rifles and muzzleloaders. All heights include the .090" thick dovetail portion itself.

| STOCK # | BEAD DIA. | HEIGHT | WIDTH | PRICE |
|--------------|-----------|--------|--------|-------------------------|
| #962-161-250 | 1/16" | .260" | Narrow | 2F12J74 \$ 14.99 |
| #962-161-251 | 1/16" | .260" | Medium | 2F12C74 \$ 14.99 |
| #962-161-310 | 1/16" | .312" | Narrow | 2F12I74 \$ 14.99 |
| #962-161-311 | 1/16" | .312" | Medium | 2F12Q74 \$ 14.99 |
| #962-161-340 | 1/16" | .343" | Narrow | 2F12I74 \$ 14.99 |
| #962-161-450 | 1/16" | .450" | Narrow | 2F12D74 \$ 14.99 |
| #962-161-571 | 1/16" | .570" | Medium | 2F12L74 \$ 14.99 |
| #962-165-310 | 3/32" | .312" | Narrow | 2F12G74 \$ 14.99 |

GUARANTEED. FOREVER. **SINCE 1939**

WILLIAMS GROOVED RECEIVER FOOLPROOF

Fits All Grooved Receiver .22's

Adjusts to fit any .22 with a receiver groove that measures .300" to .600" wide. No drilling, tapping or modifications required. Internal micrometer adjustments with positive clicks. Lock-screws secure adjustments against accidental change. Mounts low but may require a higher than standard front sight.



SPECS: Aluminum, black, anodized body. Bright steel "standard style windage and elevation screws. Blue steel aperture. FP-GR 13/4" (4.4cm) wide. $1^{2i}/_{32}$ " (4.2cm) high. Weighs $1^{i}/_{4}$ oz. (35 g). .0093" (2.4mm) aperture opening. FP-GR-TK: $2^{5}/_{32}$ " (5.5cm) wide. $1^{5}/_{8}$ " body. Blue steel "Target Knobs" adjust windage and elevation. .093" (2.4mm) aperture opening.

| #962-200-810 | Foolproof FP-GR, 2F63D74 | 74.99 |
|--------------|-----------------------------|-------|
| #962-201-606 | Foolproof FP-GR-TK, 2F72J24 | 84.99 |



WILLIAMS RIFLE FIRE SIGHT

Glowing, Fiber Optic Dots For **Faster Sight Pickup**

Easy-to-install front sights for popular centerfire and muzzleloading rifles

gather ambient light for superb visibility. The more light, the brighter the round, red beads glow; won't "wash out" even in the strongest sunlight. Narrow sights fit Williams Streamlined and Shorty Ramps. Medium sights fit most factory ramps including Marlin and Remington. Wide sights are for .22 rimfire rifles and muzzleloaders. SPECS: Blued steel. Fiber optic insert. Beads: 1/16" (1.6mm) dia. Fit nominal 3/8" dovetail. Number indicates height, letter (N, M or W) indicates base width. Height is measured from bottom of dovetail to top of sight. N Series - .250" (6.3mm) wide base. M Series - .340" (8.6mm) wide base. W Series - .531" (13.5mm) wide base.

| STOCK # | HEIGHT/WIDTH | STOCK # | HEIGHT/WIDTH |
|--------------|--------------|--------------|--------------|
| #962-564-320 | 260 N | #962-564-440 | 406 M |
| #962-564-330 | 290 N | #962-564-450 | 450 M |
| #962-564-360 | 375 N | #962-000-085 | 500 M |
| #962-564-370 | 406 N | #962-564-460 | 538 M |
| #962-564-380 | 450 N | #962-590-790 | 437 W |
| #962-564-390 | 260 M | #962-590-800 | 500 W |
| #962-564-400 | 290 M | #962-590-820 | 570 W |
| #962-564-430 | 375 M | - | |
| | | | |

| — Advise # — | Rifle Fire Sight, | 2F16L14 | \$ 18.99 |
|--------------|--------------------|---------|----------|
| — Auvise # — | Kille Fire Signit, | 2F10L14 | \$ TO.33 |

FIRE SIGHT HOOD - Protects front blade from those damaging accidental bumps. Open top allows plenty of light to reach the fiber optic rod. Fits Williams Streamlined Dovetail Ramps. SPECS: Steel, blue. .630" (16mm) diameter. 1" (2.5cm)



| WGOS REPLACEMENT REAR SLIDE/BLADE - Fits all standard |
|--|
| Williams adjustable, rear guide open sights. Aluminum blade con- |
| tains two, green, fiber optic dots; use with existing factory front or |
| choose a replacement Fire Sight Rifle Bead listed above. |

#962-000-016 Fire Sight Hood, 2F10/19......\$ 11.99

| 31 LC3. /4 dild /16 | ricigitt ority. | |
|---------------------|-----------------------------------|-------|
| #962-602-180 | 1/4" Fire Sight WGOS Slide/Blade, | |
| | 2F21R2A | \$ 2. |

| 702 002 200 | 2F21B24 | \$ 24.99 |
|-------------|------------------------------------|----------|
| 962-602-190 | 5/16" Fire Sight WGOS Slide/Blade, | |
| | 2F21A24 | 24 99 |

| Rear Rea Sight Blad Heig |
|--------------------------------|
|--------------------------------|

COMMERCIAL RIFLES

RECWANING 30-106 (EN Mausor)

| Barrel Diameter 4 | " ahead of Rec | eiver | .98 | 0 |
|-------------------|----------------|---------------|--------|------|
| Barrel Diameter a | it Muzzle | | .58 | 5 |
| Height of Factory | Ramp and Bea | id above Barr | el .70 | 0 |
| | | | | |
| FP-98 | - | | .280 | .594 |

| BROWNING | 308 AND | 270 (FN | Mauser) |
|----------|----------------|---------|---------|

| Barrel Diameter 4 Barrel Diameter a Height of Factory | ahead of Rec | | .98 | o 0 |
|---|--------------|-------|------|--------|
| FP-98 | 3/16" | 7/16" | .345 | .689 |
| WGOS-L | | 7/16" | .281 | .625 |

BROWNING AUTO RIFLE

| Barrel Diameter at N Barrel Diameter at D Height of Factory Ra | ovetail | id above Barr | .60 .87 el .56 | | |
|--|---------|---------------|----------------------|-------|--|
| WGRS-BAR WGOS-BAR- | - | 7/16" | .345 | .6895 | |
| WGOS-BAR- | | | | | |

MARLIN 39A, .22 Caliber

| Barrel Diameter 4" a Barrel Diameter 22- Height of Factory Ra | 1/2" ahead o | f Receiver | .780 .675 el .350 | 5 |
|---|--------------|------------|-------------------------|------|
| FP-39 or 5D-39 | 3/16" | 1/8" | .312 | .344 |
| WGOS-M | | 9/32" | .260 | .448 |

MARLIN 336

.640

| Barrel Diameter 4" ahead of Receiver |
|--|
| Barrel Diameter 22" ahead of Receiver |
| Height of Factory Ramp and Bead above Barrel |
| |

| | neight of ractory K | amp and bea | iu above barr | et .40 | J |
|--|---------------------|-------------|---------------|--------|--------------|
| | 5D-94/36 | 3/16" | | | .531 .500 |

REMINGTON NYLON 66, 76, 10, 11, 12

| Barrel Diameter 3" a Barrel Diameter 18" Height of Factory Ra | .62 .62 .46 | 5 | | |
|---|-------------------|-------|------|------|
| FP-760N, 5D-760N 5D-510 (for round | - | 3/8" | .281 | .563 |
| receiver) | - | 3/8" | .281 | .563 |
| WGOS-S | 1/4" | 9/32" | .281 | .469 |
| WGOS-S | 5/16" | 5/16* | .312 | .531 |
| WGOS-S | 3/8" | 3/8" | 312 | 594 |

REMINGTON 510, 511, 512

| Barrel Diameter 4-1, Barrel Diameter 23* Height of Factory Ra | .74 .61 el .29 | 5 | | |
|---|----------------------|-------------------------|---------------------|--------------|
| 5D-510 WGOS-2 or M WGOS-S or M | 3/16" 1/4" | 3/16* 9/32* 5/16* | .281 .281 312 | .375 .469 |

REMINGTON 550

| Barrel Diameter 2 | .607 | | | |
|-------------------|-------|-------|------|------|
| Height of Factory | .258 | | | |
| WGOS-S or M | 3/16" | 9/32" | .281 | .469 |

REMINGTON 552-572 BDL

| Barrel Diameter 4" ahead of Receiver .740 sarrel Diameter at Muzzle .625 Height of Factory Ramp and Bead above Barrel .570 | | | | | | | |
|--|------------------------------|-----------------------------|--------------------------|------------------------------|--|--|--|
| FP-740 AP 5D-572 WGRS-54 WGOS-M WGOS-M | - - - 1/4" 5/16" | 9/32" - 9/32" 3/8" | .281 - .312 312 | .570 .469 .570 .500 | | | |

REMINGTON 572

| Barrel Diameter 3-: Barrel Diameter 21: Height of Factory F | .61 .32 | 9 | | |
|---|----------------|-------------------------|----------------------|----------------------|
| FP-740 AP WGOS-M WGOS-M | 3/16" 3/16" | 3/16* 9/32* 3/16* | .312 .281 .375 | .406 .469 .469 |

REMINGTON 580, 581, 582, .22

| Barrel Diameter 3* Barrel Diameter 23 Height of Factory F | .62 .62 .45 | 25 | | |
|---|-------------------|-------------------------|----------------------|----------------------|
| WGRS-54 WGOS-S WGOS-S | 3/16" 1/4" | 9/32" 3/16" 9/32" | .312 .312 .312 | .500 .406 .469 |

REMINGTON 700, 725

| Barrel Diameter 20" ahead of Receiver .590 Height of Factory Ramp and Bead above Barrel .685 | | | | | |
|---|-------------------|-----------------------|---------------------|--------------|--|
| FP-70, 5D-70 WGOS-M or L WGOS-M or I | - 1/4" 3/8" | 3/8" 3/8" 7/16" | .281 .281 345 | .563 .563 | |

WILLIAMS SIGHT SELECTION CHART

| Sight | Blade Height | Ramp Height | Bead Height | Height abv. Bbl. | Sight | Blade Height | Ramp Height | Bead Height | Heig abv. B |
|---|--|--------------------------------|------------------------------|------------------------------|--|-----------------------------|-------------------------|----------------------------|----------------|
| | | TON 721, | | _ | | | RBY MAR | | _ |
| Barrel Diameter 5-1 Barrel Diameter 22" Height of Factory R | ahead of Re | ceiver | .75i .60 el .53 | 5 | Barrel Diameter 4-1 Barrel Diameter at N Height of Factory Ra | 1uzzle | | .73 .55 el - | |
| FP-70, 5D-70 WGOS-M WGOS-M WGOS-M | 1/4" 5/16" 3/8" | 3/8" 5/16" 3/8" 7/16" | .312 .312 .312 .312 | .594 .531 .594 .656 | FP-98 (Fits Right or Left Hand) MS WGOS-S WGOS-S | - 1/4" 3/8" | 7/16" 5/16" 7/16" | .312 .312 .312 | .656 .53: |
| R Barrel Diameter 4-1 Barrel Diameter 20- Height of Factory Fri Height of Factory Fri | 2/" ahead of 3/4" ahead on ont Sight abo | of Receiver ve Barrel (old | .80 .60 style) .42 | 0 5 | WIN Barrel Diameter 5" a Barrel Diameter 22- Height of Factory Fr | head of Rec 1/2" ahead o | f Receiver | AGNUM .72 .58 .26 | 4 |

.500 .500 .625 .625

.281 .281 .281 .281

REMINGTON 788

3/16° 5/16°

5/16° 7/16° 7/16°

FP-760 or 5D-570/ WGOS-M

WGOS-M WRGS-760

| Barrel Diameter 4-1 Barrel Diameter 4-1 Height of Factory Ra | .89 .58 el .82 | 7 | | |
|--|----------------------|-------|------|------|
| FP-788 | - | 5/16" | .312 | .531 |

RUGER 10-22

| Barrel Diameter at | Barrel Diameter 2" ahead of Receiver Barrel Diameter at Muzzle Height of Factory Ramp and Bead above Barrel | | | | |
|--------------------|---|---|---|-----------|--|
| FP-RU | - | - | - | .450 Bead | |
| 5D-RU | - | - | - | .450 Bead | |
| WGRS-RU | - | - | - | .450 Bead | |
| WGOS-L | 3/16" | - | - | .583 Bead | |

RUGER 44 MAGNUM

| Barrel Diameter 4-1/4" ahead of Receiver Barrel Diameter 17-1/2" ahead of Receiver Height of Factory Ramp and Bead above Barrel | | | .81 .62 el .47 | 5 |
|---|---------------|-------------------------|----------------------|----------------------|
| FP-RU, 5DRU WGOS-M WGOS-M | 3/16" 3/8" | 5/16" 9/32" 7/16" | .312 .312 .345 | .531 .500 .689 |
| WGRS-44 | - | 3/8" | .281 | .563 |

| Barrel Diameter 4- Barrel Diameter at | | | .50 | 5 |
|--|---|-------|------|------|
| WGOS-L | - | 9/32" | .312 | 500 |
| 5D-22/410 | - | 9/32" | .260 | .450 |

SAVAGE 99DL, .358

| Barrel Diameter 4-1/2" ahead of Receiver Barrel Diameter 22" ahead of Receiver Height of Factory Ramp and Bead above Barrel | | | .80 .57 el .55 | 5 |
|---|--------------------|--|----------------------|---|
| FP-99S WGOS-M WGOS-M | /GOS-M 3/16" 5/16" | | | |

SAVAGE 99E (old style)

| Barrel Diameter 3-3 Barrel Diameter 22' Height of Factory R | ahead of Re | ceiver | .870 .58 el .50 | 5 |
|---|-------------|--------|-----------------------|------|
| FP-99S | 3/16" | 9/32" | .312 | .500 |
| WGOS-L | | 3/8" | .260 | .542 |

SAVAGE 99E 308

| arrel Diameter 4- arrel Diameter 20 leight of Factory I | 1/2" ahead of 0-1/4" ahead o | of Receiver | .66 .57 | 5 |
|---|---------------------------------|-------------|------------|-----|
| FP-99S | - | 3/8" | .260 | .54 |
| WGOS-S | 1/4" | 3/8" | 281 | 56 |

SAVAGE 99R, 99EG, .300 SAVAGE

| | Barrel Diameter 22" ahead of Receiver Height of Factory Ramp and Bead above Barrel | | | 5 |
|------------------|---|----------------|--------------|--------------|
| FP-99S WGOS-L | 3/16" | 9/32" 5/16" | .260 .312 | .448 .531 |
| | • | • | | |

SAVAGE 110

| Barrel Diameter 3- Barrel Diameter 19 Height of Factory | 1-1/2" ahead c | of Receiver | .77 .57 .60 | 75 |
|---|----------------|------------------------|----------------------|----------------------|
| FP-110 WGOS-M WGOS-M | 1/4" 5/16" | 7/16* 3/8' 7/16* | .260 .281 .281 | .605 .563 .625 |

SAVAGE 340

| Barrel Diameter 3-1 Barrel Diameter 19" Height of Factory R | ahead of Re | ceiver | .82 .60 el .47 | 0 |
|---|----------------|-------------------------|----------------------|---------------------|
| FP-340 WGOS-M WGOS-M | 3/16" 3/16" | 5/16" 9/32" 5/16" | .312 .345 312 | .531 .533 531 |

| arrel Diameter at Muzzle .555 leight of Factory Ramp and Bead above Barrel - | | | | | |
|---|-------------------|-------------------------|----------------------|----------------------|--|
| FP-98 (Fits Right or Left Hand) MS WGOS-S WGOS-S | - 1/4" 3/8" | 7/16" 5/16" 7/16" | .312 .312 .312 | .656 .531 .656 | |

| Barrel Diameter 4" ahead of Receiver | | | .715 | |
|---|-------|----------------|--------------|-----|
| Barrel Diameter 21-1/2" ahead of Receiver | | | .565 | |
| Height of Factory Bead above Barrel | | | .260 | |
| FP-94 WGOS-S | 3/16* | 3/16" 9/32" | .312 .281 | .4i |

WINCHESTER 64, .30-30

| Barrel Diameter 22-: Height of Factory Ra | 1/2" ahead o | f Receiver | .56 el .43 | 5 |
|--|--------------|----------------|---------------|--------------|
| FP-94 or 5D-94/36 WGOS-M | 3/16* | 5/16" 5/16" | .281 .281 | .500 .500 |

| WINCHESTER 69 | |
|--|------|
| Barrel Diameter 2-3/4" ahead of Receiver | .782 |
| Barrel Diameter 23-1/4" ahead of Receiver | .638 |
| Height of Factory Front Sight above Barrel | .232 |
| | |

WGOS-M 3/16* 9/32" .281 .469

| WINCHESTER 70 WESTERNER, | STANDARD |
|--|----------|
| Barrel Diameter 5-1/4" ahead of Receiver | .790 |
| Barrel Diameter 22" ahead of Receiver | .613 |
| Height of Factory Ramp and Bead above Barrel | .477 |

| Barrel Diameter 4-1 Barrel Diameter 201 | | | .79 56 | |
|--|-------------|--------------|-----------|------|
| leight of Factory R | amn and Rea | ad above Bar | rel 54 | 5 |
| reignit or ructory is | ump uma bee | ad above bar | .54 | .5 |
| FP-70, 5D-70 WGOS-M | 1/4* | 3/8" 3/8" | .312 | .594 |

WINCHESTER 88

| Barrel Diameter 4- Barrel Diameter 20 Height of Factory I | " ahead of Re | ceiver | .80 .51 el .51 | 75 |
|---|---------------|----------------|----------------------|--------------|
| FP-88 WGOS-M | 3/16* | 5/16" 5/16" | .312 .312 | .531 .531 |
| WGOS-M | 3/8" | 7/16" 3/8" | .345 312 | .689 594 |

WINCHESTER 94, .30-30, .32 WIN.

| Barrel Diameter 4" al Barrel Diameter 18-1 Height of Factory Ra | L/2" ahead o | f Receiver | .74! .60i el .450 | 5 |
|---|--------------|----------------|-------------------------|--------------|
| FP-94 or 5D-94-36 WGOS-S/M | 3/16* | 5/16" 9/32" | .260 .281 | .479 .469 |

WINCHESTER 100., 243, 308

| Barrel Diameter 4-1 Barrel Diameter 20' Height of Factory R | ahead of Re | ceiver | .781 .561 el .441 | 5 |
|---|-------------|--------|-------------------------|-----|
| FP-88 | - | 5/16" | .260 | .47 |
| WGOS-M | 3/16" | 5/16" | .281 | .50 |
| WGOS-M | 3/8" | 7/16" | .345 | .68 |
| WGRS-100 | - | 3/8" | .345 | .62 |

MILITARY RIFLES

30 CARBINE

| eight of Military Fro | | | | |
|-----------------------|-------|-------|------|------|
| WGRS-M1-CAR | - | 9/32" | .312 | .500 |
| FP-30-M1 | - | 3/16" | .260 | .354 |
| Military Rear | - | 9/32" | .260 | .448 |
| WGOS-S | 1/4" | 3/16" | .312 | .406 |
| WGOS-S | 5/16* | 9/32" | .281 | .469 |

1917 FNFIFI D Barrel Diameter 4-1/4" ahead of F

| Height of Military F | | | .78 | |
|---|--------------|------------------------|----------------------|----------------------|
| FP-17 or 5D-JEMS WGOS-L WGOS-L | 1/4" 3/8" | 7/16" 3/8" 7/16" | .375 .281 .375 | .719 .563 .719 |

| Rear Sight | Rear Blade Height | Williams Ramp Height | Williams Bead Height | Tot. Frnt Height abv. Bbl. | | |
|---|-------------------------|----------------------------|----------------------------|----------------------------------|--|--|
| Garrel Diameter 4-1/4' ahead of Receiver 735 Barrel Diameter 22' ahead of Receiver 635 deright of Military Front Sight above Barrel | | | | | | |
| Po-JEMS or FP-JAP - 7/16' 260 .604 .000 .000 .000 .000 .000 .000 .0 | | | | | | |

Barrel Diameter 4-1/4" ahead of Receiver .745 .620 Barrel Diameter 22" ahead of Receiver Height of Military Front Sight above Barrel FP-JAP WGOS-M

| WGOS-M WGOS-M | 5/16" 3/8" | 3/8° 7/16° | .312 .312 | .594 .656 |
|---|------------------------------|---------------|-------------------|--------------|
| Barrel Diameter 4-1 Barrel Diameter 21" Height of Military Fr | /4" ahead of ahead of Red | ceiver | .89 .67 .46 | 5 |
| ED V KDVC | | 7/16" | 712 | 656 |

| Height of Military Fr | | .460 | | |
|---|-----------------------|---------------------------------|------------------------------|------------------------------|
| FP-A-KRAG WGOS-L WGOS-L WGOS-L | 1/4" 5/16" 3/8" | 7/16" 3/8" 7/16" 7/16" | .312 .281 .281 .345 | .656 .563 .625 .689 |
| Barrel Diameter 4-1 | | N 98 MAUS Receiver | SER .90 | 0 |

.900 .600 .485 Barrel Diameter 22" ahead of Receiver Height of Military Front Sight above Barrel FP-98 or 5D-JEMS .281 .281 .345 .563 WGOS-L 1/4" 3/8"

91, 94, 95 MAUSERS

WGOS-L

| Barrel Diameter 22" Height of Military Fr | ahead of Re | ceiver | .68 .48 | 5 |
|---|----------------------------|--------------------------------|------------------------------|------------------------------|
| FP-98 or 5D JEMS WGOS-M WGOS-M WGOS-M | - 1/4" 5/16" 3/8" | 3/8* 5/16* 3/8* 7/16* | .281 .312 .312 .312 | .563 .531 .594 .656 |

7.62 RUSSIAN M91 Barrel Diameter 4-1/4" ahead of Receive

| Barrel Diameter 2 | 2" ahead of Re | ceiver | .65 | 0 |
|----------------------------|-----------------------|------------------------|----------------------|----------------------|
| WGOS-M WGOS-M WGOS-M | 1/4" 5/16" 3/8" | 5/16" 3/8" 7/16" | .281 .281 .281 | .500 .563 .625 |
| Rarrel Diameter 4 | | 1 SMLE | 71: | 2 |

| Barrel Diameter 22" Height of Military Fro | | | .58 .74 | |
|---|--------------|-------------------------|----------------------|---------------------|
| FP-SMLE or 5D-SMLE WGOS-S WGOS-S | 1/4" 3/8" | 7/16" 5/16" 7/16" | .312 .312 .312 | 656 .531 .656 |
| | | | | |

Barrel Diameter 4-1/4" ahead of Receiver

| Height of Military Fr | Front Sight above Barrel | | .770 | | |
|---|--------------------------|-------------------------|----------------------|----------------------|--|
| FP-SMLE or 5D-SMLE WGOS-M WGOS-M | 1/4" 3/8" | 7/16" 5/16" 7/16" | .312 .312 .312 | .656 .531 .656 | |

.775

.717

.930

#5 SMLE Barrel Diameter 4-1/4" ahead of Receive

| Barrel Diameter 20- OD of Flash H Height of Military Fr | .75 | - | | |
|---|---------------|-------------------------|----------------------|----------------------|
| FP-SMLE or 5D-SMLE WGOS-S WGOS-S | 1/4" 5/16" | 9/32* 3/16* 9/32* | .260 .345 .312 | .448 .439 .500 |

'03 SPRINGFIELD '03 Barrel Diameter 4-1/4" ahead of Receiver Barrel Diameter 22" ahead of Receiver

| leight of Military Fr | .74 | 7 | | | |
|------------------------------|-------|-------|------|------|--|
| FP-'03 or 5D-JEMS WGOS | - | 9/16" | .260 | .729 | |
| Special WGOS | 3/16" | 7/16" | .312 | .656 | |
| Special 751 | 5/16" | 9/16" | .281 | .751 | |

'03-A3 SPRINGFIELD

| Barrel Diameter 22" ahead of Receiver Height of Military Front Sight above Barrel | | | | 0 |
|--|--|-------|-----|---|
| FP-'03-A3 or | | 0.000 | 740 | |

| '03-A3 | - | 9/16" | .312 | .781 |
|-------------------------|-------|----------------|--------------|--------------|
| WGOS Special WGOS | 5/16" | 9/16" | .312 | .781 |
| Special WGRS-'03-A3 | 3/8" | 9/16" 9/16" | .345 .345 | .815 .814 |

order on the web

WILLIAMS "WGRS" RECEIVER SIGHT



 Easily Installed • Compact • Rustproof • Low Profile • Lightweight • Positive Windage & Elevation Adjustments

In most cases, these sights utilize dovetail or existing screw holes on top of receiver to give guns the advantage of peep sights.

SPECS: Aluminum, black, anodized. Peep height is approximately the same as a 3/16" (4.8mm) Open Sight Blade.

| STOCK # | MODEL | FITS |
|--------------|--------------|---------------------------------|
| #962-100-700 | WGRS-700 | Remington 700, 721, 722 |
| #962-100-742 | WGRS-742 | Rem 742ADL, 760ADL; For |
| | | BDL's use FP-740AP Foolproof |
| #962-000-019 | WGRS-336 | Marlin 336 |
| #962-000-027 | WGRS-CVA Rnd | CVA with round barrel, Win. |
| | | X-140 |
| #962-000-015 | WGRS-TC | T/C Encore |
| #962-000-068 | WGRS-Savage | Savage 110 Accu-trigger (round |
| | | receiver) (for use w/538M bead) |

WILLIAMS BLADES & BASES FOR "WGOS" & "WDOS" SIGHTS

Assemble Complete Sights Or Replace Blades To Change Sight Picture

Precision-made sight bases and blades milled from high-tensile strength. rustproof alloy. Dovetailed windage and elevation adjustments have hardened gib locks. Make adjustments quickly by loosening one screw. No dovetailing of barrel necessary. Bases and blades sold



separately. Blades can also replace the aperture on WGRS sights. SPECS: Bases and blades: aluminum, black anodized finish, Bases - All models except the One Inch have .5625" c-to-c hole spacing. Small -.347" radius, fits .660" to .730" dia. barrels **Medium -** .395" radius, fits .730' to .830" dia. barrels. Large - .440" radius, fits .830" to .930" dia. barrels. X-Large - .5625" c-to-c hole spacing .475" radius, fits .900" to 1" dia. barrels. One Inch - 1" c-to-c hole spacing, .500" radius, fits 1" dia. barrels. 26mm - .550" radius, fits 1" to 1.1" dia. barrels. Blades available in 3/16" (4.8mm), 1/4" (6.3mm), 5/16" (7.9mm), and 3/8" (9.5mm) heights. Range of adjustment for each listed in table below

WGOS/WDOS BASES

| STOCK # | FOR SIGHT | FITS BARREL DIAMETER |
|--------------|-----------|---|
| #962-600-000 | WGOS | Small, .660"730" dia. |
| #962-607-000 | WGOS | Medium, .730"830" dia. |
| #962-608-000 | WGOS | Large, .830" - 930" dia. |
| #962-611-000 | WGOS | X-Large, .900" - 1" dia., .5625" c-to-c |
| | | hole spacing |

| — Advise # — WGOS Base, 2F19N54 \$ 22. | 9 | 9 | , |
|--|---|---|---|
|--|---|---|---|

| | BLADE HEIGHT & RANGE OF ADJUSTMENT | | | | | | |
|---------------|---|----------------------------|--|--|--|--|--|
| BLADE | TOTAL SIGHT HEIGHT | | | | | | |
| HEIGHT | T On WGOS Base* On WDOS Base | On WGOS Base* On WDOS Base | | | | | |
| 3/16" | .369" (9.4mm)431" (10.9mm) .281" (7.1mm)345" (8.8m | nm) | | | | | |
| 1/4" | .431" (10.9mm)493" (12.5mm) .345" (8.8mm)406" (10.3 | mm) | | | | | |
| 5/16" | .493" (12.5mm)555" (14.0mm) .406" (10.3mm)468" (11. | 9mm) | | | | | |
| 3/8" | .555" (14.0mm)617" (15.7mm) .468" (11.9mm)531" (13. | 5mm) | | | | | |
| #062 7 | 550-218 U-Notch Blade. 3/16" 2F9A59 \$: | 11 00 | | | | | |

WILLIAMS STREAMLINED DOVETAIL RAMP

Long & Graceful

Polished and Blued Steel. Screw-on models have two

attaching screws, one under sight and one on ramp. Hole spacing on Remington model matches factory drilled and tapped barrels. SPECS: Fractional height listed in table is the overall ramp height measured from top of barrel to top of ramp. Decimal height listed is measured from top of barrel to bottom of dovetail. Width of ramp is .250" (6.3mm). Supplied without hood.

| STOCK # | HEIGHT | STYLE | PRICE |
|--------------|----------------|----------|-------------------------|
| #962-020-097 | 3/16" (.0975") | Screw-On | 2F23H79 \$ 27.99 |
| #962-020-344 | 7/16" (.3445") | Screw-On | 2F23B79 \$ 27.99 |
| #962-020-469 | 9/16" (.4695") | Screw-On | 2F23H79 \$ 27.99 |

WILLIAMS SHORTY DOVETAIL RAMP

Compact & Attractive For Smaller Guns



Polished, blued steel. Hoodless. Sweat-on or screw-on. SPECS: Height shown in parenthesis in chart is from top of barrel to bottom of dovetail. Width of ramp is .250" (6.3mm). Made only in heights

| STOCK # | HEIGHT | STOCK # | HEIGHT |
|---------------------------|---------------|--------------|-------------|
| \$ 962-010-032 | 1/8" (.032) | #962-010-282 | 3/8" (.282) |
| 1 962-010-094 | 3/16" (.0945) | | |

- Advise # — Shorty Ramp, 2F19K54.....\$ 22.99

WILLIAMS ONE-PIECE FIRE SIGHT RAMP



Replaces Fragile, Plastic Ramps With Sturdy, One-Piece Metal No need to worry about breaking a sight

ramp when you're busting through heavy brush. Solid, one-piece, CNC machined aluminum ramp attaches with one 6-48 screw and gives you a

bright, glowing, sight picture. Fire red, fiber optic rod glows brightly using only available natural light for high visibility. SPECS: CNC machined aluminum, black. Fire red fiber optic rod. #70105 height = .410", fits barrel dia. of .625"; #70220 - height = .485", fits barrel

dia.of .875". Gunsmith installation recommended. #962-000-065 #70105 Fire Sight Ramp, 2F16/14......\$ 18.99 #962-000-066 #70220 Fire Sight Ramp, 2F16A14 18.99

WILLIAMS REAR DOVETAIL FIRESIGHT

Replaces 3/8" Dovetail Rear Sights With Fiber Optics

Highly visible fiber optic rear sight fits lever actions, .22 rimfires, and most American-made rifles with the standard 3/8" dovetail. Bright green dots are easily seen under most light conditions and help you get on target guickly. Adjustable for windage and elevation. No gunsmithing required. SPECS: Aluminum, matte black. Green fiber optic rod. Approximately 5/16 from bottom of blade to bottom of notch. Fits 3/8" dovetails.

WILLIAMS -

RIFLE FIRE SIGHT SIGHTS

Upgrade Your Factory Sights With Easy-To-See, Fiber Optics

All sets feature a bright red, fiber optic, front sight and fully adjustable peep or U-notch, rear sight. U-notch, rear sight sets use the highly accurate, 3-dot pattern with two green, fiber optic dots at the rear for sharp contrast and guick sight acquisition in all light conditions. No drilling or tapping required for most rifle models. Dovetailed front and rear sights may require minor fitting.

REMINGTON FIRE SIGHTS - Fiber optic, U-notch, rear sight at-

taches to the factory, rear sight ramp to improve visibility; adjusts for windage and elevation. Contrasting, red, front sight really stands out for fast pickup



and alignment. 2003 & Earlier fits Remington rifles and muzzleloaders with dovetailed, front sight ramps, plus all Remington shotguns. 2003 & Later fits Remington rifles and muzzleloaders manufactured from 2003 to present with 1-piece, ramped front sights. SPECS: Aluminum, black anodized.

#962-565-300 Remington Fire Sights, 2F24A64...... \$ 28.99 #962-000-056 2003 & Later Rem. Fire Sights. 2F24J64 28.99

REMINGTON GHOST RING FIRE SIGHTS - Bright, high contrast fiber optic sights with large aperture, rear ghost ring provide fast, accurate sight alignment in all light conditions. The more light, the brighter the beads glow. Front sight has a single red insert, rear ghost ring has two green inserts to form an easy-to-align, 3-dot sight picture. Fits Remington rifles and muzzleloaders from 2003 and earlier with 3/8" dovetail front sight ramps, plus all Remington shotguns with 3/8" dovetail front sight ramps. Set includes front and rear sights.

SPECS: Steel front 3/8" dovetail sight. Aluminum rear sight. Black, matte finish. Fiber optic insert. Bead - 1/16" (1.6mm) dia. Ghost Ring - .15" (3.8mm) dia. aperture.

#962-000-083 2003 & Earlier Ghost Ring Fire Sights,

RUGER® 10/22® FIRE SIGHTS - High visibility, fast to pickup, sight systems for the Ruger® 10/22°. WGRS features low profile, quide receiver, peep sight and red, fiber optic, front sight. 3-Dot has U-notch rear blade with green dots, red front sight. Adjustable for windage and elevation.

SPECS: Aluminum, black anodized. Front - .530" high, 1/16" red

fiber optic bead. Fits Ruger 10/22 only #962-633-300 WGRS-RU22 Fire Sights, 2F40F79 \$ 47.99

#962-602-130 3-Dot Ruger Fire Sights, 2F20B39 23.99

MARLIN & WINCHESTER **LEVER ACTION** - For Marlin and Winchester lever action rifles. Replaces factory front



SPECS: Aluminum, black anodized. Fits all Winchester and Marlin lever actions with ramped front sights. #962-602-170 Dovetail Fire Sights, 2F33C14 \$ 38.99

MARLIN RIMFIRE FIRE SIGHTS - Dovetail sights replace the factory open sight sets on your Marlin rimfire. U-shaped, green, fiber

WILLIAMS MUZZLELOADER FIRE SIGHT

Fast, Accurate Sighting For All Light Conditions





Contrasting red front and green rear, fiber optic dots offer quick sight alignment; won't wash out in bright light, improve contrast in low light. Fully adjustable, "U"-notch, rear sight gives precise alignment for long range shots. Replaces factory sights with only minor fitting. Machined from aircraft aluminum for years of service. SPECS: Aluminum body, black, matte finish. Bead - .058" (1.2mm) diameter, .89" (22.6mm) long. TC - Thompson Center. Octagon model fits newer guns with .836", c-to-c hole spacing. Remington sets are available with a standard notch rear sight or a .15" (3.8mm) diameter ghost ring rear sight. Models to fit 2003 & Earlier muzzleloaders with 3/8" dovetail front sight

ramps or 2003 & Later muzzleloaders with 1-piece ramped front sights.

| STOCK # | FITS | PRI | CE |
|--------------|-----------------------------------|---------|----------|
| #962-622-560 | TC Octagon Barrel | 2F32M29 | \$ 37.99 |
| #962-565-300 | Rem 2003 & Earlier, Notch | 2F24A64 | \$ 28.99 |
| #962-000-056 | Rem 2003 & Later, Notch | 2F24J64 | \$ 28.99 |
| #962-000-083 | Rem 2003 & Earlier, G. Ring | 2F31N44 | \$ 36.99 |
| #962-000-084 | Rem 2003 & Later, Ghost Ring | 2F31M44 | \$ 36.99 |
| #962-622-600 | Traditional Lightning Fire, Buck- | 2F32B29 | \$ 37.99 |
| | hunter, Timberridge & Cabela's | | |

optic, rear sight contrasts well with the red, front bead. Adjustable for windage and elevation.

SPECS: Aluminum, black anodized. Fits Model 60, 915Y, 925, 925M, 981T, and 983T.



#962-000-092 Marlin 60 Fire Sights, 2F23I79.....

WGOS REPLACEMENT SLIDE/BLADE -

Rear slide/blade combo fits all standard size, Williams, adjustable, rear guide, open sight bases. Converts traditional, rear iron sights into Fire Sights. Aluminum blade contains a single, U-shaped, green, fiber optic rod for 2-dot accuracy. Use with existing factory front sight or with fiber optic.



Williams Rifle Sight Bead found elsewhere in catalog. Available in three heights.

SPECS: Aluminum, black anodized, 3/16" (4.8mm), 1/4" (6.4mm), and 5/16" (7.9mm) high.

| #962-000-081 | 3/16" WGOS Slide/Blade, 2F21M24 | \$ 24.99 |
|--------------|------------------------------------|----------|
| #962-602-180 | 1/4" Fire Sight WGOS Slide/Blade, | |
| | 2F21B24 | 24.99 |
| #962-602-190 | 5/16" Fire Sight WGOS Slide/Blade, | |
| | 2F21A24 | 24 99 |

WGOS REPLACEMENT SLIDE/GHOST RING - Rear slide/ghost

ring sight fits all standard size Williams adjustable rear guide open sight bases. Features a large light gathering ghost ring with two green, fiber optic dots for sharp contrast and quick sight acquisition in all light conditions. Ring aperature naturally centers to draw the eye to the front sight for faster target acquisition and improved



accuracy, Fully adjustable for windage and elevation, Rugged, lowprofile aluminum sight has an anodized finish for resistance against scratches. Use with existing factory front sight or with fiber optic, Williams Rifle Sight Bead found elsewhere in catalog.

SPECS: Aluminum, black anodized. 1/4" (6.4mm) high. Aperature - 5/12" (3.9mm) I.D. #962-000-082 1/4" WGOS Slide/Ghost Ring, 2F8M79 ... \$ 10.99

BROWNELLS PAGE 322

GUARANTEED. FOREVER. **SINCE 1939**

WILLIAMS FOOLPROOF & 5D RECEIVER SIGHTS —

Dependable, Accurate Sights - Available For Most Guns

FOOLPROOF RECEIVER SIGHTS - Internal micrometer adjustments lock positively to prevent accidental movement of sight setting. No obstructions to impair and blot out shooter's field of vision. Weighs only 1½ oz. Standard hole spacing to fit guns factory drilled and tapped for receiver sight. Foolproof features adjustment screws for windage and elevation.



Foolproof-TK comes equipped with target knobs. SPECS: Alum., black, anodized. Steel screws. See chart below

| | 5-D Sight , <i>2F35M69</i> | \$ 41.9 |
|--------------|-----------------------------------|---------|
| - Advise # - | Foolproof Sight, 2F63C74 | 74.9 |

EOOLPROOF TARGET KNOBS - All Foolproof sights (except TK models) use the Short Elevation Knob. The Long Elevation Knob is for use with Foolproof-TK target sights. † indicates Short Windage Knob, †† indicates Long Windage Knob. The Elevation Gib Lock Knob fits both standard Foolproof and Foolproof-TK models.



| DW. | adjustments. Windage and elevation ad- |
|----------------|---|
| \$ 41.99 | justments are easily made by loosening |
| 74.99 | screws, moving the sight, and re-tight- |
| - | ening the screws. Excellent for hunting rifle applications that don't require regular |
| 4 | tweaking of the sight adjustment settings. |
| Target Knob | Stop screw provides an accurate guide, so to absolute zero upon detaching and reattage. |

Stop screw provides an accurate guide, so the 5D sightwill return to absolute zero upon detaching and reattaching to the gun. Standard hole spacing for easy, secure mounting.

#962-157-520 Target Windage Knob, Long, 2F00CNM . . \$ 6.99

#962-157-530 Target Windage Knob, Short, 2F00HJN . . 6.99

#962-157-240 Target Elev. Knob, Long, 2F00FAL 7.99

#962-157-250 Target Elev. Knob, Short, 2F00LUL...... **7.99**

#962-000-079 Elevation Gib Lock Knob. 2F00KQM..... 7.99

5D RECEIVER SIGHT - Same depend-

able, accurate construction as the Fool-

proof models but without micrometer

SPECS: Aluminum, black, anodized. Steel screws. Advise Stock # from chart below.

| – Advise # – | 5-D Sight. | 2F35M69 | \$ 41.99 |
|--------------|------------|-------------|---------------|
| — Advise # — | 5-D Signt. | 2F.3.3/VID9 | . 5 41.99 |

| MODEL | STK | (# 5D | STK# FO | OLPROOF | STK# FOOL | .PROOF-TK |
|---|--------------|----------|--------------|--------------|--------------|-------------|
| BENJAMIN, 340, 342, 347 (need higher front sight) | #962-150-790 | 5D-SH | NA | | NA | |
| BROWNING, B-92 | NA | | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| HIGGINS, 30/30 Lever | #962-150-094 | 5D-94/36 | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| MARLIN, A-1 | #962-150-081 | 5D-81 | NA | | NA | |
| 30-30 | NA | | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| 36 | #962-150-094 | 5D-94/36 | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| 336 | NA | | NA | | #962-000-062 | FP-336-TK |
| 94 | #962-150-094 | 5D-94/36 | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| 93 | NA | | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| .44 Mag & 44 | #962-150-094 | 5D-94/36 | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| SEARS Centerfire Lever | #962-150-094 | 5D-94/36 | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| SHERIDAN, Model C | #962-150-790 | 5D-SH | NA | | NA | |
| THOMPSON/CENTER Contender | NA | | #962-200-860 | FP-T/C †† | NA | |
| Hawken/Renegade | NA | | #962-200-815 | FP-Hawken †† | NA | |
| WINCHESTER 9422 | #962-150-094 | 5D-94/36 | NA | | NA | |
| 55 & 65 | NA | | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| 64 & 94 | #962-150-094 | 5D-94/36 | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |
| 94 Angle Eject | NA | | #962-200-194 | FP-94SE† | NA | |
| 241 | NA | | #962-200-036 | FP-94/36† | #962-000-039 | FP-94/36-TK |

^{*}Mounts in rear scope mount holes. †Short windage knob. ††Long windage knob.

XS SIGHT SYSTEMS RIFLE APERTURE REAR SIGHT POST FRONT SIGHT

Fast Sighting With Ghost-Ring Apertures

The potential accuracy of aperture sights with the sighting speed of open sights. All-steel construction.

APERTURE REAR SIGHTS - Easy-to-install, fully machined, allsteel sights with windage and elevation-adjustable bases are pre-machined to fit quickly using the rear scope base holes on many popular rifles. A fast, accurate sight for brush hunting applications. Adjustments are secured with dual setscrews.



SPECS: Steel, blue, matte finish. .191" (4.8mm) diameter aperture. Marlin Lever and Rem. 700 fit factory rear hole pattern. Mauser requires drilling and tapping, use .350" (8.8mm) front sight.

| STOCK # | FITS | PRICE | |
|--------------|----------------------------|---------|----------|
| #006-103-300 | Marlin 30AS, 336, 1894 | 6K57B59 | \$ 63.99 |
| #006-103-095 | Marlin 1895 in 45-70, .444 | 6K57D59 | \$ 63.99 |
| #006-103-098 | Mauser 98 | 6K57J59 | \$ 63.99 |

<u>POST FRONT SIGHTS</u> - Modified post front sight with vertical white line insert is fast and easy to see in all light conditions.

SPECS: Steel, blue, matte finish. Fits nominal ³/s" x 375° dovetail. 100° (2.54mm) wide post has .040° (1mm) wide stripe, heights listed in chart. Heights measured from top of blade to bottom of dovetail. Includes Test Post Sight.




| STOCK # | HEIGHT | PRICE |
|--------------|----------------|-------------------------|
| #006-113-300 | .300" (7.62mm) | 6K30H59 \$ 35.99 |
| #006-113-350 | .350" (8.89mm) | 6K30P59 \$ 35.99 |

XS SIGHT SYSTEMS LEVER ACTION —— APERTURE REAR & FRONT SIGHT SETS

Combines The Accuracy Of Aperture Sights With The Speed Of Open Sights

Easy-to-see post front and ghostring rear get you on target fast for brush hunting and action



SPECS: Rear – Steel, blue, matte finish. Win. 92 and Win. 94 Top Eject require drilling and tapping of receiver. Front – Steel, blue, matte finish. Fits .250° or .340° wide front bases or nominal ³/₆° dovetail, as noted. Post – .100° (27mm) wide vith .030° (76mm) wide stripe.

| STOCK # | | FITS |
|--------------|-----------|--|
| #006-000-140 | 0 | Marlin 336 w/ 3/8" dovetail barrel |
| #006-000-141 | 0 | Marlin 1895SS, 444SS w/ 3/8" dovetail barrel |
| #006-000-143 | () | Marlin 39A ,w/ .250" & .340" wide front base |
| #006-000-145 | () | Win. 94 w/ 20-24" dovetail barrel |

- Advise # - Aperture & Post Sight Set, 6K81/69..... \$ 85.99

MARLIN INTEGRAL POST AND BASE SET - Onepiece front base, plus a fully adjustable ghost ring rear sight for Marlin lever guns. Hunters and competitive shooters alike will benefit from the faster sighting offered by the .191° and .230° inside diameter rear apertures and .100° wide,



SPECS: Steel, black, matte finish. 336/1894/30AS Ghost Ring Set - Fits Marlin 336, 1894, and 30AS with .700° c-to-c front ramp hole spacing. 1895 Lever Rail Ghost Ring Sets - For XS Lever Rail applications only. Models available for Marlin 1895 and 336

| #006-000-024 | (| 336/1894/30AS Ghost Ring Set, 6K94C99 | 99.99 |
|--------------|----------|--|-------|
| #006-000-162 | (| 1895 Lever Rail Ghost Ring Set, 6K89H99 | 99.99 |

DRC WINGED 1895 GHOST-RING SIGHT SET - Give your 1895

Guide Gun an extremely durable sight that withstands the toughest hunting and field use. Sturdy steel wings protect the rear sight body from damage. Windage and elevation adjustable, ghost-ring rear furnished with .191" and .230" diameter apertures. One-piece from tests and been be highly wife.



piece front post and base has highly visible, 100" wide, white line, front post.

SPECS: Steel, black, matte finish. 1895 - Fits Marlin 1895 with .700" and 1.00" c-to-c front ramp screws. .528" high front sight measured from top of barrel to top of blade.

#006-000-037 O DRC 1895 Marlin Sight, 6K120B59. \$ 133.99

MARLIN 1894/1895/336/308MX LEVER RAIL - Lightweight scope

rail mounts to Marlin centerfire lever gun without drilling and trapping. Accepts Weaver-style or Picatinny accessories, including the Marlin 1894, 1895 or Marlin 336/308MX Lever Rail Ghost Ring



set (above). Extra-long rail gives plenty of versatility in mounting scope directly over the receiver or forward over the barrel for intermediate eye relief optics or red dot sights. Requires removal of factory rear sight. Gunsmith installation recommended. SPECS: Aluminum, black, matte finish. 11' (27cm) long. 830' (21mm)

XS SIGHT SYSTEMS AK-47
TRITIUM EXPRESS SIGHT SET

Big Dot Front Sight Puts You On Target Fast; Fully Adjustable Rear Sight For Improved Accuracy



High visibility sight combination easily replaces the

factory sights on your AK-47 or variant for fast sight acquisition in high stress or low light conditions. Machined steel set includes an adjustable white stripe, V-notch rear sight and a genuine Trijicon brand titrium lamp with large white ring for the front. Front sight completely replaces the factory windage drum and front sight post. Large, single setscrew in the tangent rear sight provides fine adjustments for elevation; dual setscrews in the dovetailed rear V-notch block securely lock-in your windage settings. Includes installation tools, thread locking agent, and detailed instructions.

SPECS: Steel, black, matte finish, Front Sight - 160' (4.1mm) diameter white ring with 0.75' (1.9mm) diameter tritium lamp, Rear Sight - .140' (3.6mm) high vertical white stripe. Fits AK-47 and clones.

#006-000-161 AK-47 Tritium Express Set, 6K115C19 \$ 127.99



XS SIGHT SYSTEMS RIFLE WEAVER BACKUP SIGHT

Excellent Insurance Against Scope Failure

Ghost-ring aperture is a fast, alternative, open sight that will save your hunt if your scope fails. Perfect for use on in-line muzzleloaders when hunting no-scope areas. Attaches in just seconds, without gunsmithing, to any Weaver-style base. Fully adjustable for windage and elevation. Includes front Test Post.

SPECS: Steel, blue, matte finish. .191* (4.8mm) diameter aperture. Weaver - .275' (7mm), High Weaver - .500* (12.7mm) from top of base to center of anetture.

#006-105-000 Weaver Backup Sight, 6K62H99.... \$ 69.99 #006-105-001 High Weaver Backup Sight, 6K66M59. 73.99

wide. 3 oz.(85g) weight. Includes mounting hardware.

| .99 | |
|-----------------------------------|--|
| Marlin 1894 Lever Rail, 6K57D59 | 63.90 |
| Marlin 1895 Guide Gun Lever Rail, | |
| 6K57L59 | 63.90 |
| Marlin 336/308MX Lever Rail, | |
| 6K57I59 | 63.90 |
| | Marlin 1894 Lever Rail, 6K57D59 § Marlin 1895 Guide Gun Lever Rail, 6K57L59. Marlin 336/308MX Lever Rail, 6K57I59. |

MARLIN 1894/1895/336/308MX LEVER RAIL SIGHT SYSTEM

Convenient kit combines the lightweight Lever Rail one-piece scope rail with backup iron sights for mounting on your Marlin lever rifle without drilling and trapping. Rear ghost ring is fully adjustable for windage and elevation, with interchangeable .191" and .230" diameter apertures for fine-tun-



ing accuracy. One-piece front sight has .100" wide white-line post. SPECS: Lever Rail - Aluminum, black, matte finish. 11" (27cm) long, .830" (21mm) wide. 3 oz. (85g) weight. Includes mounting hardware. Sights - Steel, matte black finish. Front sight: .100" wide, .528" high measured from top of barrel to top of blade. 1895 fits Marlin 1895 with. 700" (17.8mm) and 1" (2.5cm) c-to-c front ramp screws. 336 fits round barrel Model 336 only.

| #006-000-167 | Marlin 1894 Lever Rail Sight System, 6K145G80 |
|--------------|---|
| #006-000-166 | Marlin 1895 Lever Rail Sight System, 6K145A80 |
| #006-000-168 | Marlin 336 Lever Rail Sight System, 6K145H80 |

order on the web

MARBLE IMPROVED PEEP TANG SIGHT



Interchangeable Posts For Quick Change From Short- To Long-Range Configuration

Gives the single-shot or lever gun shooter the period looks of a traditional tang-mounted peep sight, plus new adjustability features that allow fast changes from short- to long-range settings. Great for the cowboy shooter who

wants to use the same gun in cowboy competition and long-range side matches, or as an alternative to vernier-type sights on singleshot rifles used in BPCR and other long-range competitions. Each sight comes with a post that is the correct height to regulate the same as the original factory iron sights. Click adjustable for windage and elevation; each click is approximately 1/4" of adjustment at 100 yards. For larger elevation changes, you can easily swap in a higher or lower post (available below); choose a lower post for close-in shooting and a taller post for longer ranges. All components are precision CNC machined from 4140 steel, with critical parts heat-treated for extra strength. To purchase, find your gun in the left column, then find the correct sight kit and mounting screw set for it in the right column. Use with Marble's front sights, available separately. SPECS: Steel, blued. Drilling and tapping may be required for installation on older guns. Sight kit includes base, Low (L) or Standard (S) height post, 1/2" O.D. aperture disc with .055" peep, and Allen wrench.

| FITS | POST | STK# SIGHT | STK# SCREWS |
|--------------------------------|------|--------------|--------------|
| American Arms 1874 Sharps | S | #579-000-166 | #579-000-124 |
| Armi 1874 Sharps | L | #579-000-167 | NA NA |
| Browning 1885 w/tang | L | #579-000-167 | #579-000-132 |
| Browning 1885, 78 w/o tang | L | #579-000-167 | NA |
| Browning 1886 | S | #579-000-174 | NA |
| Browning 1892, 53, 65 (Japan | L | #579-000-167 | NA |
| mfr) | | | |
| Browning 71LT | S | #579-000-174 | NA |
| Cimarron 1866 | S | #579-000-166 | NA NA |
| Cimarron 1873 | S | #579-000-166 | NA NA |
| EMF 1874 Sharps (not | L | #579-000-167 | NA |
| carbine) | | | |
| H&R Buffalo Classic | L | #579-000-167 | NA |
| Henry .22LR Lever (H001 & | L | #579-000-167 | NA |
| H001T, not H001V) | | | |
| Henry Big Boy .30-30, | S | #579-000-166 | NA |
| .357/.38, .44 Mag. & .45 Colt | | | |
| Marlin 336, incl. 444SS, | S | #579-000-176 | #579-000-114 |
| 1895G, 1895SS | | | |
| Remington Model 1, 2, 5 | S | #579-000-173 | NA NA |
| Rossi 1892, 65 | L | #579-000-167 | #579-000-101 |
| Rossi 59, 62 | L | #579-000-167 | NA NA |
| Shiloh Sharps 1874 & New | L | #579-000-167 | NA |
| Model 1874 | | | |
| Springfield 1870 | L | #579-000-167 | NA NA |
| Taylor 1874 Sharps | L | #579-000-167 | NA NA |
| Thompson/Center Scout | L | #579-000-167 | |
| Uberti 1873 (not incl. Hunter) | S | #579-000-166 | #579-000-100 |
| Uberti 1885 | L | #579-000-167 | NA |
| Uberti 1886 | S | #579-000-166 | #579-000-100 |
| Uberti 1892 | L | #579-000-167 | #579-000-100 |
| Uberti Henry | L | #579-000-167 | NA |
| Varner Favorite | S | #579-000-166 | #579-000-124 |
| Winchester 1866 | L | #579-000-167 | #579-000-102 |
| Winchester 1873 | L | #579-000-167 | NA |
| Winchester 1876 & 1886 | S | #579-000-174 | NA |
| (original) | | | |
| Winchester 1885 (original) | L | #579-000-167 | NA NA |
| | | | |

| FITS | POST | STK# SIGHT | STK# SCREWS |
|-------------------------------------|-----------|--------------|--------------|
| Win. 1885 Low- & High-Wall | L | #579-000-167 | #579-000-100 |
| (Japan mfr) | | | |
| Winchester 1890, 62, 64, 65 | L | #579-000-167 | #579-000-117 |
| Win. 1892 (original) & 1894 | L | #579-000-167 | #579-000-102 |
| (all, exc22 cal) | | | |
| Winchester 1906 | L | #579-000-167 | |
| Winchester 53, 55 | L | #579-000-167 | |
| Marlin 1893 & 1894 (original | | NA | #579-000-124 |
| models made prior to 1932 | | | |
| only) | | | |
| Henry Golden Boy .22LR | | NA | #579-000-100 |
| Win. 1886 (Japan), Browning 1886 | | NA | #579-000-112 |
| Henry Lever Action .22S/L/LR | | NA | #579-000-105 |
| & .22 Mag. | | | |
| Henry Golden Boy .22LR | | NA | #579-000-105 |
| (H004) & .22 Mag (H004M) | | | |
| Marlin 1889, 1892, 1893, | | NA | #579-000-124 |
| 1894, 25, 27, 29, 39, 39A (old/ | | | |
| original models) | | | |
| Glenfield 30, Marlin 39, 1892, | | NA | #579-000-114 |
| 1894 (Cowboy), 1897, 1897 | | | |
| Annie Oakley | | | |
| Marlin 39A, 39AS, 39M, | | NA | #579-000-114 |
| 39TDS (current models) | | | |
| Marlin/Glenfield 30A, 30AS, | | NA | #579-000-114 |
| 30GT | | | |
| Rem. No. 1 Rolling Block | | NA | #579-000-100 |
| (current mfr) | | | |
| Savage 30G Stevens Favorite | | NA | #579-000-124 |
| Taurus M62 | | NA | #579-000-100 |
| Henry Big Boy .44 | | NA | #579-000-102 |
| Uberti Rolling Block | | NA | #579-000-100 |
| Win. 62, 1890, 1906 | | NA | #579-000-117 |
| Winchester 1895 (original) | | NA | #579-000-116 |
| - Advise # - Peep Tang S | Sight, 90 | G115C19 | \$ 143.99 |
| - Advise # - Mounting S | | | |
| Sight, 9G6L | 39 | | 7.99 |

| Advise # — | Peep Tang Sight, 9G115C19 | \$ 143.99 |
|------------------------------|------------------------------------|-----------|
| Advise # — | Mounting Screw Set For Marble Tang | |
| | Sight, 9G6L39 | 7.99 |

SIGHT POSTS - The Improved Tang Sight's quick-release post system makes it easy to replace the post that came with your sight with a higher or lower one for targeting at different ranges. Choose a lower post for close-in targets or a taller post for longer ranges. Post height is also click adjustable for fine-tuning when sighting in; each click represents 1/4" of adjustment at 100 yards. A jam nut locks the elevation, so you can remove and reinstall a post without losing settings.

SPECS: Steel, blued. Heights measured from base of post to center of aperture. Low - 1.085" to 1.415" height adjustment range. 1/2" aperture disc with .055" peep. Standard - 1.341" to 1.876 height adjustment range. Medium - 1.875" to 2.965" height adjustment range. 3/4" aperture disc with .032" peep.

| #579-000-096 | Tang Sight Post, Low, 9G38C24 | \$ 44.99 |
|--------------|---|----------|
| #579-000-097 | Tang Sight Post, Std, 9G40D79 | 47.99 |
| #579-000-098 | $\textbf{Tang Sight Post, MedRange}, \ 9G59C19$ | 73.99 |

Stock numbers shown in red indicate the product is made in the U.S.A.

This information is not available for all products at time of catalog production, but will be regularly updated on our website.



MARBLE TANG SIGHT

Period Looks, Superb Accuracy

Adds a touch of authenticity to pump and lever action rifles, whether they're used for hunting or Cowboy Action Shooting. Provides better sight definition and faster target acquisition in the field or on the range. Locates the aperture closer to the eve for a clear sight picture; longer sight radius increases accuracy. All steel construction with micrometer adjustments for windage and elevation. Folds to the rear for stor-

age. Mounting screw set must be purchased separately. SPECS: Steel, blued. Older guns may require drilling and tapping. Includes (2) ½" diameter apertures: .055" (1.4mm) and .102" (2.6mm) size holes. and (1) 3/4" diameter aperture with .032" (.81mm) hole. Savage 99 will not fit late rifles with top safety. Late rifles with safety at trigger will require drilling and tapping. Mounting screw sets sold separately.

TANG SIGHT & REPLACEMENT SCREWS

| STK# | STK# SCREWS | FITS |
|--------------|----------------|--|
| #579-009-800 | #579-000-132 | Browning 1885 w/tang |
| #579-009-807 | #579-000-101 | Rossi 1892, 65 |
| #579-000-015 | #579-000-124 | Savage 99 (see price below) |
| #579-000-003 | #579-000-105 | Uberti and Cimarron 1873 |
| #579-000-149 | #579-000-132 | Uberti 1885 |
| #579-009-808 | #579-000-102 | Win. 53, 55, 64, 1892 (original), 1894 (except .22) |
| #579-000-001 | #579-000-100 | Win. 1885 Low Wall (Japan) |
| #579-000-085 | #579-000-108 | Win. 94 (tang safety), 94 Legacy, 94 Trails End™ |
| NA | #579-000-114 | Glenfield 30, Marlin 39, 1892, 1894 (Cowboy), 1897, 1897 Annie Oakley |
| NA | #579-000-105 | Henry Lever Action .22S/L/LR & .22 Mag. |
| NA | #579-000-100 | Henry Golden Boy .22LR |
| NA | #579-000-102 | Henry Big Boy .44 |
| NA | #579-000-124 | Marlin 1893 & 1894 (original models made prior to 1932 only) |
| NA | #579-000-114 | Marlin 336/1895, 444S |
| NA | #579-000-124 | Marlin 25, 27, 29, 39A, 1892, 1897 (original) Ballard #8 Union Hill, Sav- |
| | UETO 000 400 | age 30G, Stevens Favorite |
| NA NA | #579-000-100 | Remington Model 1, 2, 5 |
| NA | #579-000-105 | Uberti and Cimarron 1866 |
| NA NA | #579-000-117 | Win. 62, 1890, 1906 |
| NA | #579-000-100 | Win. 1885 Hi-Wall (Japan), TC Scout |
| NA | #579-000-112 | Win. 1886 (Japan), Browning 1886 |
| — Advise # — | Marble Tang Si | ght, 9G109P64 \$ 128.99 |

LYMAN **NO. 2 TANG SIGHT**

- Advise # - Mounting Screw Set For Marble Tang

Sight, 9G6L39.....

The Original No. 2; Now Back In Production

The original folding tang sight that increases sight radius for greater potential accuracy with your favorite lever action rifle. Sight features rugged, all-steel construction, knurled locking

screw, index marks on aperture post, .093" quick sight and .040" large disc apertures. Includes rear stock screw and front tang screw. SPECS: Steel, blue. C-to-c 2.200", fits Winchester Model 94. Some rifles may require drilling and tapping. Can be adapted to other rifles with tangs.

#539-050-002 Winchester 94 No. 2 Tang Sight, 5K84M99.....\$ 94.99



MIDWEST INDUSTRIES MARLIN 1894/1895 GHOST RING RAIL SIGHT SETS



Standard Set

Speed AND Precision of Your 21st Century Tactical Lever Gun

Ya know, pardner.... lever action rifles were the "Black Rifle" of their era, the latest in "tactical" and personal defense firearm technology. And even now, more than a century and a half since the Henry Repeating Rifle revolutionized the Personal Defense Weapon landscape, the lever action rifle can STILL be a formidable weapon. Hence, MI's line of tactical upgrades for them, including these sight rails for the venerable Marlin '94 and 1895 rifles. This kit includes matched front and ghost-ring rear iron sights - still one of the fastest-to-acquire sight pictures. That rear sight clamps securely on top of an assembly that includes 2.5" (1894) or 4" (1895) of MIL-STD 1913 Picatinny rail, so you can further boost your Marlin into Buck Rogers territory by mounting a red dot sight on it. If your red dot of choice is an Aimpoint T1 or T2, you can get Midwest's "T1" rear rail assembly with a built-in mount for it instead of the Pic rail. The ghost-ring setup includes a wide windage and elevation adjustment range so you can guickly re-zero the rifle when you change to a different ammo load (sight adjustment tool included). The rear base assembly is made of 6061 T6 aluminum with a matte black hardcoat anodized finish, while the front sight and rear sight ghost ring are

| black-finished | steel. 💻 | |
|----------------|---|-----------|
| #100-043-860 | Marlin 1894 Ghost Ring Rail Sight Set, 2A114C29 | \$ 124.95 |
| #100-043-861 | Marlin 1894 T1 Ghost Ring Sight Set, 2A114K29 | 124.95 |
| #100-043-862 | Marlin 1895 Ghost Ring Rail Sight Set, 2A114H29 | 124.95 |
| #100-043-863 | Marlin 1895 T1 Ghost Ring Sight Set, 2A114A29. | 124.95 |

SMITH ENTERPRISE WESSON & HARRINGTON LONG **RANGE SIGHT**

Extremely Versatile Buckhorn Sight; Sight, Base & Screws, All-In-One

Precision-machined, buckhorn, rear sight and base include screws that fit the holes in your Wesson & Harrington rifle for drop-on, no gunsmithing installation. Slider has a detent that lets you feel each adiustment: setscrew locks into place. Ladder has side markings so you can

easily repeat the right yardage settings. Drift adjustable for windage setscrew locks your setting.

SPECS: Machined steel, blued finish. Sight - Ladder has approximately 1²⁷/₆₄" (3.6cm) height adjustment; Buckhorn aperture ⁵/₁₆" (8mm) I.D. Base - 19/64" (7.5mm) high from bottom of receiver to top of base, 23/4" (7cm) long, 5/8" (15.9mm) wide.

#851-000-045 Wesson & Harrington Sight,

GUARANTEED. FOREVER.® **SINCE 1939**

— PEDERSOLI –

COWBOY TARGET RIFLE SIGHTS

Superb Long-Range Accuracy & The Right Period Styling

Single-shot rifles of the Old West are capable of tremendous range and accuracy, but fixed, factory sights rarely allow these guns to reach their full potential. In the days before compact scopes, target shooters and hunters seeking tack-driving accuracy relied on precisely adjustable vernier tang-mounted rear sights and globe front sights. Pedersoli offers BPCR silhouette shooters, competitors, and Cowboy Action shooters taking part in Schuetzen side matches affordable, high-quality replica sights that function just like the originals. Get your Winchester 1885, Rolling Block, Sharps, Ballard, Trapdoor Springfield, or other vintage single-shot rifle performing—and looking—its best.

"CREEDMOOR" REAR TANG SIGHTS -

Named after the famous range on Long Island that hosted many long-range rifle competitions in the 1870s and '80s, the Creedmoor ladder-type sight is fully adjustable for windage and elevation and works equally well on cartridge rifles and muzzleloaders. Sight is precision machined from steel and attaches to tang with supplied setscrews and folds down when not in use. The **Universal** model

is available in middle-range 2" and long-range 3" heights. The windage adjustment mechanism is on the eyepiece, allowing the eyepiece to dropped close to the base for close-in shots. The **Soule** model provides maximum adjustablity to fit any hunting or target shooting conditions. Elevation is adjustable in precise increments of 1 MOA, and one full turn of the windage knob moves the point of aim left or right by 2½ MOA in ½ minute increments. Large knurled knob at the sight base allows fast, accurate return to center or previous setting. **Goodwin Style** sights

a 3"
n is obed del gor e in the ght led urn like Goodwin Style

to center or previous setting. **Goodwin Style** sights offer precise windage adjustments with 1.26" movement for high wind conditions. Elevation adjustment totals 3.94"

for long-range shooting and the tilt screw on the base lets you keep the sight perfectly vertical, no matter the elevation or angle. Goodwin-Style structure lets you reach the rifle's chamber with any cleaning device and inspect the barrel between shots.

SPECS: Steel blued Floogated rear mounting hole allows installation.

SPÉCS: Steel, blued. Elongated rear mounting hole allows installation on most rifles. Drilling and tapping of tang may be required. Distance between mounting holes 2.20*2.29* (5.6-5.8cm). Mounting screws and installation instructions included.

| #100-002-377 | Univ. Middle Range 2" Tang Sight, 4A131P99 | \$ 164.99 |
|--------------|--|-----------|
| #100-002-376 | Univ. Long Range 3" Tang Sight, 4A131174 | 154.99 |
| #100-002-379 | "Soule" Middle Range 3" Tang Sight, 4A190A39 | 223.99 |
| #100-002-380 | "Soule" Long Range 4" Tang Sight, 4A214K19 | 251.99 |
| #100-010-691 | Goodwin Style Tang, 4A192N09 | 225.99 |

SPIRIT LEVEL TUNNEL FRONT SIGHT W/INSERTS - Windage-

adjustable, tunnel front sight comes with 12 inter-changeable inserts so you can choose the sight picture that's best for the distance and range of your target. The

spirit level helps you hold the rifle completely upright to eliminate inaccuracies caused by tilting to the left or right. Perfect companion for the Creedmoor Rear Sights.

SPECS: Steel, blued. 1" (2.8cm) OAL, 113/32" (3.6cm) maximum width at adjustment knobs. Fits 3/8" (9.5mm). 60° dovetail. Instructions included.

<u>VARIABLE APERTURE HADLEY-STYLE EYEPIECE</u> - Rotating, detent-locking disc in the eyepiece lets you select one of eight aperture sizes to match your sight setting to current lighting condi-

SMITH ENTERPRISE M-95 LONG RANGE SIGHT

Authentic Cowboy Action Look; Great For Long Distance Shooting

Versatile, CNC-machined, steel sight lets you shoot both long and short distances. Flipped up, the ladder adjusts from 100-1100 yards; flipped down, the flat top, V sight provides fast target acquisition for

v sight provides last target acquisition for shorts short shots. Ball detents provide an audible and felt click for each graduation on the ladder. Fits rifles with a */a" dovetail. \$\bigsim SPECS: Steel, black oxide finish. 2\(\frac{1}{2}\) (5.4cm) long. Ladder provides \(1^{22}\)/cs (3.4cm) height adjustment. Fits rifles with a */a" (9.5mm) dovetail.

#851-000-046 M-95 Long Range Sight, 1E147M89....\$ 173.99



MARBLE TRITIUM SHOTGUN SIGHT

Gets You On Target Quickly In Low & Regular Light

Machined steel sight has an eye-catching Tritium insert to provide a fast sight picture in low light and an easy-to-acquire white ring for daylight. White ring is recessed to protect it from being scratched and to ensure proper light reflection from any angle.

SPECS: Steel, blued, matte finish. Approximately .32" (8.1mm) long, 1/12" (4.8mm) wide, .21" (5.4mm) high. 3/12" (2.4mm) shank length. See price line for thread diameter.

| #579-000-078 | 6-48 Tritium Shotgun Sight, 9G28C89 | \$ 33.99 |
|--------------|---|----------|
| #579-000-080 | 5-40 Tritium Shotgun Sight, 9 <i>G30E3</i> 9 | 37.99 |

tions for optimum accuracy. Change settings with a flick of your thumb; no cumbersome disassembly or loosening and tightening of the eyepiece. Soft rubber ring minimizes pain from accidental contact with eyepiece on recoil. Fits both Universal and Souletype Creedmoor sights.

SPECS: Steel, blued. 1.25" (3.1cm) diameter. #100-002-381 "Hadley"-Style Eyepiece, 4A00KRM.... \$ 73.99

FOLDING FRONT SIGHT - Serves as a globe sight for long-range shooting when raised, or you can fold it down and use the built-in blade for close work. Ball/detent mechanism positively locks sight in folded or extended position. Fits rifles with 3/s", 60° dovetails.

SPECS: Steel, blued, and natural-finish brass. Fits ³/₈" (9.5mm), 60° dovetail.

#100-002-383 Folding Front Sight, 4A60P34..... \$ 70.99

TUNNEL FRONT SIGHT W/INSERTS - Tunnel front sight comes

with 12 inserts letting you choose the best sight picture for your shooting conditions. Works great with Creedmoor rear sights. Steel construction for long life and matte finish cuts glare. Inserts lock into plce with knurled, threaded cap.



SPECS: Steel, matte blue finish. Sight – "/s" (3cm) OAL. 5/8" (1.5cm) wide. Fits 3/8" 60° dovetail.

| #100-010-696 | Tunnel Front Sight W/Inserts, | |
|--------------|-------------------------------|----------|
| | 4A41.164 | \$ 48.99 |

BRADLEY™ SIGHT BEAD

The Original "Bead-On-A-Block"



Standard Bradley - Places the front sight bead on a block of steel for positive indexing, greater surface area and increased strength. Available in red and white colored plastic or gold brass beads. Solid Brass Bradley - Uniform yellow brass (gold) or white brass (silver) beads with positive-stop skirts.

SPECS: Standard Base - steel, blue. Bead - plastic, red, or white. Brass Beads - gold or silver. Metric beads are all white color.

STANDARD BRADLEY BEADS

| STK# EA. | STK# 3-PAK | BEAD SIZE | TPI | SHANK LENGTH | |
|--------------|---------------|----------------------|--------|-----------------|---------|
| #146-184-011 | #146-184-031 | 1/8" | 3-56 | 5/32" | Red |
| #146-184-012 | #146-184-032 | 1/8" | 3-56 | 5/32" | White |
| #146-184-013 | NA | 1/8" | 3-56 | 5/32" | Gold |
| #146-186-011 | #146-186-031 | 1/8" | 6-48 | 5/64" | Red |
| #146-186-012 | #146-186-032 | 1/8" | 6-48 | 5/64" | White |
| #146-186-013 | NA | 1/8" | 6-48 | 5/64" | Gold |
| #146-187-012 | #146-187-032 | 1/8" | 6-48 | 9/64" | White |
| #146-532-412 | #146-532-432 | 5/32" | 3-56 | 5/32" | White |
| #146-532-712 | #146-532-732 | 5/32" | 6-48 | 7/64" | White |
| #146-532-812 | #146-532-832 | 5/32" | 6-48 | 9/64" | White |
| #146-532-912 | #146-532-932 | 5/32" | 8-40 | 1/8" | White |
| - Advise # - | Standard Brad | l ey Bead, ea | ch, 6[| 06N74 | \$ 8.99 |

— Advise # — Std Bradley Bead, 3-pak, 6D18P74 24.99 METRIC BRADLEY BEAD

| STK# EA. | STK# 3-PAK | BEAD SIZE | TPI |
|--------------|--------------|-----------|-------|
| #146-000-001 | #146-000-005 | 1/8" | 2.5mm |
| #146-000-002 | #146-000-006 | 1/8" | 3mm |
| #146-000-004 | NA | 5/32" | 3mm |
| | | | *** |

Advise # — Metric Bradley Bead, each, 6D9I74.....\$12.99
Advise # — Metric Bradley Bead, 3-pak, 6D26G24... 34.99

BRASS SKIRTED BEADS


| STK# EA. | STK# 3-PAK | TPI | COLOR | SIZE |
|--------------|-----------------------|------|---------------|-------|
| #146-003-013 | #146-003-033 | 6-48 | Gold | 1/8" |
| #146-010-113 | #146-010-133 | 3-56 | Gold 1 | |
| #146-020-114 | #146-020-134 | 3-56 | Bright Silver | 1/16" |
| NA | A #146-005-033 5-40 (| | Gold | 1/8" |
| NA | #146-030-135 | 3-56 | Dull Sliver | 1/16" |
| | | | | |

MARBLE SHOTGUN SIGHT

3 Styles of Thread-In Sights

EXPERT TYPE - A beautiful sight for most ribs. Shoulders on sight make for easy installation.

SPECS: Bead: ¹/s" (3.2mm). Shank length: ³/s" (2.4mm). Gold bead with 3-56 thread or Ivory (white plastic) bead with 3-56 or 6-48 thread.



EXPERT FIBER OPTIC - A bright, eye catching, fiber optic sight for ribs. Shoulders on sight make for easy installation. SPECS: Bead: .0700" (1.7mm) dia. Shank length: */s²" (2.4mm). Thread size: 3-56 or 6-48. Color: Green or Orange.

| | ro. cotor. arcerror orange. | |
|------------------|-----------------------------|--------|
| STK# 3-56 THREAD | STK# 6-48 THREAD | COLOR |
| #708-305-331 | #708-305-631 | GREEN |
| #708-305-332 | #708-305-632 | ORANGE |
| | | |

- Advise # - Expert Fiber Optic Sight, 9G7N99...... \$ 9.99

TRUGLO GLO-DOT XTREME SHOTGUN SIGHT

High-Visibility Glowing Dot Makes the Most of Ambient Light

Light-gathering fiber-optic rod presents a bright, glowing aiming dot for better visibility in both bright and low light hunting conditions. Comes with four dif-

ferent magnetic bases with different internal mounting dimensions that fit a variety of ventilated ribs. Polymer base snaps onto the rib and is held firmly in place with a high-strength magnet for quick installation without screws. (May also be installed by drilling and tapping rib, screws not included.) Does not require front bead removal. Includes one red, green, yellow, and amber fiber optic rod. Rods are easily interchanged using thumb and finger pressure. Notch in base uses factory bead to locate sight correctly along bore axis. Two sets of magnets allow mounting sights on two shotguns with different width ventilated ribs. Includes pocket sized, steel case for convenient storage. Universal fit for all shotguns equipped with '/.a" (6.4mm), '3/.s" (7.9mm), '3/.s" (9.5mm), or '1/.s" (12.7mm) wide ventilated ribs. Includes one base of each size.

SPECS: Universal fit for all shotguns equipped with $^1/^a$ (6.4mm), $^5/^a$ (7.9mm), $^3/^a$ (9.5mm), or $^1/^a$ (12.7mm) wide ventilated ribs. Bases - Plastic, black. (1) $^2.260^\circ$ (6.5mm), (1) $^3.30^\circ$ (8.4mm), (1) $^4.20^\circ$ (10.7mm), (1) $^5.20^\circ$ (13.2mm) internal dimension. 2 (5.1cm) long. Rods - Polymer, (1) red, (1) green, (1) yellow, (1) amber. $^{15}/^a$ (2cm) long x.060° (1.5mm) dia. Includes (2) sets of magnets 6 steel carry case.

#902-000-124 Glo-Dot Xtreme, 2K22B94.....\$ 26.99



BROWNELLS SHOTGUN SIGHT CONVENIENCE KIT



The Tools & Sights You Need To Install/Replace Sight Beads

Everything you need to achieve a Professional shotgun sight repair or installation. Each kit includes the right drill bit and bottoming tap, plus sight(s) to help you clean up existing threads or install a sight with a larger, stronger shank. The **Brownells 6-48 Kit** features two, #4 brass front beads. Each **Bradley** kit has an Ivory, Bradleytype front sight.

SPECS: Bradley sights have 3/32" (2.38mm) long shanks.

| , | | | |
|--------------|----------------------|--------------|----------|
| #078-021-048 | 6-48 Brownells Kit, | 8G11A69 | \$ 12.99 |
| #078-021-256 | 3-56 Bradley Sight K | it, 8G11H04 | 12.99 |
| #078-021-248 | 6-48 Bradley Sight K | (it. 8G00BDH | 15.99 |

TRUGLO SHOTGUN
STARBRITE DELUXE SIGHT

5-40 tpi, 6-48 tpi,





| STOCK# | THREAD SIZE | COLOR | PRICE |
|--------------|-------------|-------|-----------------|
| #902-000-048 | 3-56 | Red | 2K8F79 \$ 10.99 |
| #902-000-049 | 3-56 | Green | 2K8D79 \$ 10.99 |
| #902-000-050 | 5-40 | Red | 2K8D49 \$ 9.99 |
| #902-000-052 | 6-48 | Red | 2K7B64 \$ 8.99 |
| #902-000-053 | 6-48 | Green | 2K8L79 \$ 10.99 |

order on the web

brownells.com

BROWNELLS SHOTGUN SIGHT KITS

SHOTGUN SIGHT KIT "A"



TWO KITS THAT COMPLEMENT EACH OTHER, A TOTAL OF 160 PRECISION, ECONOMICAL, GOOD-LOOKING, REPLACEMENT SHOTGUN BEADS

| SHOTGUN SIGHT KIT "A" CONTAINS: | | | | | | | |
|---------------------------------|-----------|--------------|-------------------|-------|--|--|--|
| No. | Head Dia. | Thread Shaft | Drill & Tap Sizes | Color | | | |
| 1 | .067 | 3 - 56 | No. 45 - 3-56 | G | | | |
| 2 | .130 | 3 - 56 | No. 45 - 3-56 | G | | | |
| 3 | .175 | 3 - 56 | No. 45 - 3-56 | G | | | |
| 4 | .175 | 6 - 48 | No. 31 - 6-48 | G | | | |
| 5 | .067 | 3 - 56 | No. 45 - 3-56 | W | | | |
| 6 | .130 | 3 - 56 | No. 45 - 3-56 | W | | | |
| 7 | .175 | 3 - 56 | No. 45 - 3-56 | W | | | |
| 8 | .175 | 6 - 48 | No. 31 - 6-48 | W | | | |

SHOTGUN SIGHT KIT "B" CONTAINS: Head Dia. Thread Shaft Drill & Tap Sizes Color 21 6 - 48 No. 31 - 6-48 G 22 6 - 48 No. 31 - 6-48 G 130 23 .130 8 - 40 No. 28 - 8-40 G 24 .175 8 - 40 No. 28 - 8-40 G 25 .067 6 - 48 No. 31 - 6-48 W 26 .130 6 - 48 No. 31 - 6-48 W No. 28 - 8-40 W 27 .130 8 - 40 28 .175 8 - 40 No. 28 - 8-40 W

SHOTGUN SIGHT KIT "B"



Brownells Shotgun Sight Kit "A" is a practical, economical assortment of top-quality, replacement shotgun sights. The workmanship is superb, being done on the most modern and up-to-date machinery in the U.S.A. The sight globes are true spheres - not lop-sided as those found on many other sights at a higher price. The threads are cut onto the shank, and are clean, sharp and well-machined for the best possible fit. Shanks are threaded right up to the base of the bead so you can set the sight exactly onto the barrel.

Your choice of sights in the Kit is extremely wide. There are 2 shank sizes, 3 bead sizes and 2 bead colors, giving you a total of 8 different sights to choose from so you can fit nearly any gun that comes into the shop.

The two shank sizes are **3-56** and **6-48**. Size 3-56 is one of the most widely used shanks in the industry and will fit most guns having threaded sight holes. The 6-48 shaft was chosen for the alternate size to be used when the original hole must be redrilled and tapped - or where there is no hole at all - because 6-48 is the firearm industry standard screw size, and every gunshop in the country will have the drill and tap on hand to make the new hole.

Bead sizes are .067, .130 and .175, (the most popular sizes), giving your customer the choice of small, medium or large beads. In addition, each bead size is available in **Gold** color - machined from finest brass; or **White** color - machined from high tensile aluminum alloy. Neither color will bleed at the heels, wear off with hard use, or chip and peel, as almost all enameled sights eventually do.

Brownells Shotgun Sight Kit "A" comes to you very attractively displayed in a clear plastic counter case. Each individual sight number is in its own plainly identified box on a black tray. There are 10 sights of each number, giving you a total of 80 sights in the Kit - 40 Gold and 40 White - a complete inventory of top-quality shotgun sights with an absolute minimum of capital invested.

Don't pass up the opportunity to cash-in on the shotgun sight replacement market. For an unbelievably low investment you can have a complete, correctly balanced and assorted inventory of 80 superb shotgun sights, each carrying Brownells guarantee of perfect workmanship and materials. Don't let yourself get caught short when you can have them on hand so easily. Order your Brownells Shotgun Sight Kit 'A' today!

SPECS: Brass and Aluminum Beads in 31/2" (8.9cm) x 7" (17.8cm) clear plastic box.

| #080-532-000 Shotgun Sig | it Kit "A", total of 80 sights in Count | er Case, 8K52D49 | \$ 69.99 |
|--------------------------|---|------------------|----------|
|--------------------------|---|------------------|----------|

SINGLE PAK REFILL SIGHTS FOR KIT "A"

| STOCK # | NO. | STOCK # | NO. | STOCK # | NO. | STOCK # | NO. |
|--------------|-----------|------------------------------|-------|--------------|-----|--------------|---------|
| #080-532-129 | 1 | #080-532-131 | 3 | #080-532-133 | 5 | #080-532-135 | 7 |
| #080-532-130 | 2 | #080-532-132 | 4 | #080-532-134 | 6 | #080-532-136 | 8 |
| — Advise # — | Single Pa | ak Shotgun Sight Refills, 81 | K2F99 | | | | \$ 3.99 |
| - Advise # - | 10 Pak S | hotaun Siaht Refills, 8K18E | 74 | | | | 24.99 |

10 PAK REFILL SIGHTS FOR KIT "A"

| STOCK # | NO. | STOCK # | NO. | STOCK # NO. | STOCK # | NO. |
|--------------|--------|-----------------------------|-----|-----------------------|--------------|----------|
| #080-532-001 | 1 | #080-532-003 | 3 | #080-532-005 5 | #080-532-007 | 7 |
| #080-532-002 | 2 | #080-532-004 | 4 | #080-532-006 6 | #080-532-008 | 8 |
| — Advise # — | 10 Pak | Shotaun Sight Refills 8K18F | 74 | | | \$ 24 99 |

Brownells Shotgun Sight Kit "B" is truly the natural and logical companion to the original Kit "A" - giving you all the sights that Kit "A" doesn't contain, but that you need to have for a really versatile and complete replacements hotgun sight inventory. Plus, in Kit "B," we took the practical step of making the White beads out of stainless steel. Stainless is tronger, won't crush or distort when the beads are installed, does not have to be removed when the gungoes into the hot bluing solution (and won't dissolve and ruin your bluing bath once it's in there!)!! Plus, the stainless won't break off at the top of the shank, stays shiny forever, stands up to tougher use in the field, and generally a lot better sight.

But, the real advantage of Kit "B" is that by combining it with Kit "A", you can now have a selection of shank sizes unequaled among shotgun sights. So, if you get a gun in your shop with a badly misshapen, worn or stripped-out sight hole, you will have a bead of exactly the same size, but with a shank one size larger. Replacement is then just a simple matter of drilling out the hole to the next size larger, tapping, and inserting the new bead.

The most important thing is that the Kit saves you time, giving faster work turnaround in the shop, which makes you more money. It also eliminates "patching-up" the original hole (which often then requires repairing the blue, too) and redrilling and tapping for the original size shank. And, it gets your customer back in the field sooner which makes him happy, and makes you look good! Like the original Kit "A", the workmanship is superb, the sight globes are true spheres, the threads are cut onto the shank, so they are clean, sharp, and give the best possible fit. And, they are threaded right up to the base of the bead so you can set the sight exactly onto the barrel.

Thread sizes are **6-48** and **8-40** - two of the most common and popular thread sizes in the gun industry, so everyone has the necessary drills and taps. The bead sizes are **.067**, **.130** and **.175**, again the most popular sizes, and the same as those used in Kit "A".

The **Gold** beads are machined from finest brass; the **White** beads from tough stainless steel. Because these are solid metal beads, they cannot bleed, chip, peel or have the color wear off.

As the companion to Kit "A", Kit "B" also comes in a clear plastic counter case. Each individual sight number is in its own clearly identified box on a black tray. There are **10 sights of each number**, giving you a **total of 80 new sights**. By itself, a complete inven- tory of 3 very popular sizes in 2 colors, with 6-48 and 8-40 shanks; but as a companion to Kit "A", an unbeatable assortment of the most versatile and useful shotgun sight beads available anywhere. And, right at your fingertips, ready to install for your customers. Order your Brownells Shotgun Sight Kit "B" today.

SPECS: Brass and Stainless Steel Beads in 31/2" (8.9cm) x 7" (17.9cm) clear plastic box.

| #080-532-100 | Brass/SS Shotgun Sight Kit "B", | , total of 80 sights in Counter Case, | 8K55P99\$ 69. ! | 99 |
|--------------|---------------------------------|---------------------------------------|------------------------|----|
| | SI | NGLE PAK REFILL SIGHTS FOR KI | Т "В" | |

| STOCK # | NO. | STOCK # | NO. | STOCK # | NO. | STOCK # | NO. |
|--------------|----------|------------------------------|------|--------------|-----|--------------|-------|
| #080-532-137 | 21 | #080-532-139 | 23 | #080-532-141 | 25 | #080-532-143 | 27 |
| #080-532-138 | 22 | #080-532-140 | 24 | #080-532-142 | 26 | #080-532-144 | 28 |
| Adviso # | Cinalo I | Pak Shotaun Sight Bofills 94 | 2500 | | | - | Ċ Z C |

10 PAK REFILL SIGHTS FOR KIT "B"

| STOCK # | NO. | STOCK # | NO. | STOCK # | NO. | STOCK # | NO. |
|--------------|--------|-----------------------------|-----------------|--------------|-----|--------------|----------|
| #080-532-121 | 21 | #080-532-123 | 23 | #080-532-125 | 25 | #080-532-127 | 27 |
| #080-532-122 | 22 | #080-532-124 | 24 | #080-532-126 | 26 | #080-532-128 | 28 |
| — Advise # — | 10 Pak | Shotgun Sight Refills, 8K18 | A <i>74</i> | | | | \$ 24.99 |

.146" - 48 TAP

A special three-flute tap for the oversized Poly-Choke Extra Long Shank (5/16") and Bev-L-Blok sights. Use .125" (1/6") drill with this tap.

#080-598-146 .146"- 48 Taper Tap, 8K24K92... \$ 29.99

LYMAN SHOTGUN SIGHT



#539-111-028 No. 11 Rear Sight, each, 5K6J99.......\$7.99
#539-101-012 No. 10D Front, Screw-in, w/wrench,
5K6G99..............799

SHOTGUN SIGHT THREADS

These sizes are correct to the best of our knowledge, however, sizes may vary with year, country of manufacture, etc. **Browning**, 3mm-5 (Metal bead), 3-56 (Ivory bead), Franchi, M3.0x0.50; Ithaca, 6-48; Marlin, 3-56; Mossberg, 5-40; Remington, 6-48; Ruger®, 3-56; Smith & Wesson, M2.5x0.45; Weatherby, 3-56; Winchester, 3-56.

N.E.C.G. SHOTGUN SIGHT BEAD

Mammoth Tusk For Look Of A Traditional Ivory Bead

This meticulously crafted front bead is made from genuine Mammoth ivory to give a fine shotgun the look of traditional elephant ivory, without violating international trade restrictions. Practical, too, because it gives a clean, easy-to-see, glare-free, white dot in all light conditions.

SPECS: Turned Mammoth ivory, natural finish. .157" (4mm) dia. bead. Undersized 6-48 thread; secure with epoxy adhesive.

dia. bead. Undersized 6-48 thread; secure with epoxy adhesive.

#661-104-004 4mm Sight Bead, 1F18I10.....\$20.99

GUARANTEED. FOREVER.
SINCE 1939

BROWNELLS SHOTGUN SIGHT BEAD KIT "C" WITH SHOULDERS —

Shouldered Beads Install To The Right Height Every Time; Popular Sizes In Brass & Stainless Steel

| | SHOTGUN SIGHT KIT "C" CONTAINS: | | | | | | | |
|-----|---------------------------------|--------------|-------------------|-------|--|--|--|--|
| No. | Head Dia. | Thread Shaft | Drill & Tap Sizes | Color | | | | |
| 10 | .130 | 3 - 56 | No. 45 - 3-56 | G | | | | |
| 11 | .130 | 6 - 48 | No. 31 - 6-48 | G | | | | |
| 12 | .175 | 3 -56 | No. 45 - 3-56 | G | | | | |
| 13 | .175 | 6 - 48 | No. 31 - 6-48 | G | | | | |
| 14 | .067 | 3 - 56 | No. 45 - 3-56 | W | | | | |
| 15 | .130 | 3 - 56 | No. 45 - 3-56 | W | | | | |
| 16 | .175 | 6 - 48 | No.31 - 6-48 | W | | | | |
| 17 | .175 | 3 - 56 | No. 45 - 3-56 | W | | | | |



Brownells Shotqun Sight Kit "C" is a must have for any gunsmith or sporting goods store looking to save valuable time and really please their customers. We have taken everything that's great about our Shotgun Sight Kits "A" and "B" - like their unparalleled selection of high quality and size- popular sight beads- and added a special feature to make the beads in Kit "C" fast, easy, and convenient to install... everytime. Every sight bead in Shotgun Sight Kit "C" has the advantage of skirted shoulders. What this means to you, the professional gunsmith or the sporting goods store owner, is you'll never have to get out your mike or calipers again to ensure you've installed the sight to its proper height. No more guesswork either! Because when the skirted shoulder reaches the barrel, it provides a positive stop that lets you know the sight is at its optimum height. Every sight from Shotgun Sight Kit "C" installs with fool-proof ease - saving you both valuable shop time and, even more important, the nightmare of upsetting a valuable customer. Not only will customers be pleased with the installation you do, they'll also love the huge selection of sizes and styles from which to choose. We selected the most popular sizes from our Shotgun Sight Kits "A" and "B", because we know that's what your customers will come in and ask you for. Plus, we know how important it is to offer different styles to please as many shooters as possible. That's why Kit "C" offers each size bead in both Gold and White. It provides the perfect selection; Gold brass for a classy, traditional look many shotgun owners are partial to and White stainless steel for a sight bead so strong it even stands up to hot bluing. Thread sizes include 3-56 and 6-48 with bead diameters of .067", .130", and .175" to give your customers the choice of small, medium and large beads. Also, for easy storage and quick identification, we've followed the same, convenient layout of Kits "A" and "B" to make it as simple as possible to find the sight you need. Kit "C's" plastic counter case is divided into eight compartments to keep the beads organized and right at your fingertips. Plus, if you put this great-looking kit on your counter for your customers to see, it's a great way to create more business by reminding people to replace broken or damaged sight beads. Brownells Shotgun Sight Kit "C" is everything you've been looking for; a huge selection, superb quality, and now the convenience of skirted shoulders. Order this time-saving, customer pleasing kit today and enjoy the speed, precision, and ease with which each of these sights installs. SPECS: Brass and Stainless Steel Beads in 3¹/₂" (8.9cm) x 7" (17.9cm) clear plastic box.

| #080-000-080 | Brass/SS Shotgun Sight Kit "C", | 8K59G49 | 69.99 |
|--------------|---------------------------------|---------|-----------|

SINGLE PAK SHOULDER BEAD FOR KIT "C"

| STOCK # | NO. |
|--------------|-----|
| #080-001-001 | 10 |
| #080-001-002 | 11 |

| STOCK # | NO. |
|--------------|-----|
| #080-001-003 | 12 |
| #080-001-004 | 13 |
| | |

| STOCK # | NO. |
|--------------|-----|
| #080-001-005 | 14 |
| #080-001-006 | 15 |

| STOCK # | NO. | STOCK # | NO. | STOCK # NO. | STOCK # | NO. |
|--------------|------------|--------------------------|--------|------------------------|--------------|---------|
| #080-001-001 | 10 | #080-001-003 | 12 | #080-001-005 14 | #080-001-007 | 16 |
| #080-001-002 | 11 | #080-001-004 | 13 | #080-001-006 15 | #080-001-008 | 17 |
| — Advise # — | Single Pal | k Shouldered Bead, each, | 8K3I74 | | | \$ 4.99 |

10-PAK SHOULDER BEADS FOR KIT "C"

| STOCK # | NO. |
|--------------|-----|
| #080-000-117 | 10 |
| #080-000-118 | 11 |
| | |

| STOCK # | NO. |
|--------------|-----|
| #080-000-119 | 12 |
| #080-000-120 | 13 |

| STOCK # | NO. |
|--------------|-----|
| #080-000-121 | 14 |
| #080-000-122 | 15 |
| | |

| STOCK # | NO. |
|--------------|-----|
| #080-000-123 | 16 |
| #080-000-124 | 17 |
| | |

CARLSON'S HIGH VISIBILITY SHOTGUN BEAD



in all types of hunting conditions. On dark or cloudy days the white bead is fast and easy to see. On bright, sunny days the fluorescent red bead remains visible in even the brightest

SPECS: Plastic bead, steel base, blued. 3-56 or 6-48 thread.

| #155-400-003 | 3-56 White High Vis. Bead, <i>5E5D59</i> | \$ 6.99 |
|--------------|---|---------|
| #155-400-004 | 3-56 Red High Vis. Bead, <i>5E6F74</i> | 8.99 |
| #155-400-001 | 6-48 White High Vis. Bead, 5E5C59 | 6.99 |
| #155-400-002 | 6-48 Red High Vis. Bead, 5E6J74 | 8.99 |



MARBLE **#223 MID-RIB SHOTGUN BEAD**

Installs Easily, Ensures Perfect Sight Alignment

Tapered, ivory-color, mid-rib bead helps prevent can-ting the gun or aiming over the top of the front bead. Stake-on design installs easily at center of barrel or 12" to 16" from muzzle. Drill a #45 hole, follow with #226 Bead Sight Reamer, and press-fit in place. SPECS: Ivory-colored, .080" (2mm) diameter.

#579-223-000 #223 Ivory Mid-Rib Sight, 9G5P24 \$ 6.99

#226 BEAD SIGHT REAMER Tapers and de-burrs after drilling hole for Marble #223 Mid-Rib

Shotgun Bead.

SPECS: Steel. 1" (25mm) long, 1/8" (3.2mm) diameter.

#579-226-000 #226 Bead Sight Reamer, 9G8B17...... \$ 9.99

HIVIZ SHOTGUN — FIBER OPTIC SIGHT

Improves Target Visualization

Light gathering polymer rod works in low light, as well as bright daylight, to give you an easy-tosee dot. Four colored rods let you change sights to fit shooting con-

ditions. Locating fingers on each end center the sight on your rib; two strong magnets prevent movement.

SPECS: Base - Plastic, black, Rods - Polymer, red, green, vellow, orange. .170" (4.3mm) diameter sighting dot. **M-300 -** fits ribs ⁷/₃₂" (5.5mm) to ⁵/₁₆" (8.2mm) wide. **M-400 -** Fits ribs ⁵/₁₆" (8.2mm) to ⁷/₁₆" (11.3mm) wide.

#638-300-000 M-300 Fiber Optic Sight, 8C17L59..... \$ 21.99 #638-400-000 M-400 Fiber Optic Sight, 8C17M59.... 21.99

COMP SIGHT - Light gathering, polymer rod provides an easy-to-see dot in low light and bright daylight. Steel base replaces front bead, screws on for a secure mount. Includes eight interchangeable light pipes, three orange, three green and two white in three diameters: .105", .115" and .130" for competition, law enforcement



and field use. Four sight mounting screws are supplied to fit nearly all shotgun ribs, plus a rotary carrying case for storing light pipes and spring release key. SPECS: Steel base, matte black. 1" (2.5cm) long. Screw/fits: 3-56" for Ru-

ger, Beretta/Benelli, Browning Target Citori, Krieghoff; M3X.5" for Browning Gold and Citori Field; 5-40" for Mossberg; 6-48" for Remington (with threaded bead) and SKB sporting models.

#638-000-001 Comp Sight, 8C28G04....


TOM BUSTER II SIGHT SET - Fits shotguns with vent ribs between 11/64" and 7/16" wide and a removable front sight. Rear has two green dots and adjusts for windage and elevation. Front has one green and one orange, interchangeable rod. Sights fit a variety of shotguns and kit includes five installation screws.



SPECS: Rear Sight - Steel base, black. 21/2" (63mm) long, 3/4" (19mm) wide ¹/₈" (3.1mm) high. Front sight – 2½" (63mm) long, ¼" (6.3mm) wide, ¼ high. Includes: 3-56; 3mm x .5; 3mm x .6; 5-40; 6-48. Gunsmith installation recommended.

#638-000-038 Tom Buster II Sight Set, 8C25A49..... \$ 33.99

FLAME SIGHT - Replaces the front bead with a highly visible fiber optic rod on all shotguns with a ventilated rib. Screws are included to fit all front bead thread sizes. An easy way to upgrade to a bright front sight for hunting, target shooting, or tactical use.



ePipe. Replaces front sight bead on all vent ribbed shotguns. #638-000-040 Flame Sight, Green, 8C12B74 \$ 14.99

SPARK II SIGHT - Highly visible, fiber optic front sight features a unique, interchangeable mounting post system for easy installation on most major brands of shotguns with plain or ribbed barrels. Pre-tapped, steel sight base accepts five, included mounting posts to accommodate shot-



guns drilled and tapped for 6-48, 5-40 or 3-56, plus the popular 3mm x .5 or 3mm x .6 metric sizes. Bright, fiber optic LitePipe provides superior light transmission from dawn 'til dusk, perfect for low light hunting conditions, as well as competition and self defense guns where fast sight acquisition is paramount. Requires drilling and tapping on shotguns with factory, press-fit bead sights. SPECS: Sight Base - Steel, blue finish. .204" (5.2mm) long x .137" (3.5mm) wide. Bead - Polymer, available in Red or Green. .362" (9.2mm) long x .106' (2.7mm) diameter. Sight Height - .167"(4.2mm) high from top of barrel to top of bead. 6-48 fits Remington, Weatherby, SKB and Ithaca. 3-56 fits Browning Citori target guns, Benelli, Beretta, Ruger, and Winchester. 5-40 fits Mossberg. 3mm x .5 fits Browning Gold and Citori field guns. 3mm x

SCATTERGUN TECHNOLOGIES REMINGTON TRAK-LOCK® II GHOST RING SIGHTS

Tritium Provides Excellent Sight Acquisition, Day Or Night

Self-illuminating Tritium front sight dot combined with a large, lightgathering rear ghost ring provides ex-



tremely fast sight acquisition during day or low light conditions. Rear ghost ring is available with or without tritium. Trak-Lock rear sight features a single set-screw for windage and elevation adjustments. Rugged, low-profile steel body has black parkerized finish for durability. **TF12** contains tritium dot front sight with standard rear ghost ring. **TF12FO** contains Tritium front sight only. Fits 12 gauge. SPECS: Steel, black parkerized. Fits plain barrel Rem. 870, 1100, 11-87,

SPT-12. Adapts to fit other guns. Requires drilling and tapping of receiver; front sight epoxies over factory front. Includes rear mounting screws. TF12 - Tritium front sight with standard rear ghost ring. Fits 12 gauge. TF12FO - Tritium front sight only. Fits 12 gauge.

| #800-110-000 | TF12 Tritium Front w/Standard Rear, 12 | |
|--------------|---|--------|
| | gauge, 8Z111P34 | 130.99 |
| #800-000-009 | TF12F0 Tritium Front Sight, only, | |
| | 8Z60H34 | 70.99 |

TRIJICON SHOTGUN ADJUSTABLE NIGHT SIGHT



Low Light, Tactical Sight System

Rugged, steel rear sight has quick-to-use, single screw adjustment for windage and elevation that

won't work loose with recoil. Ghost ring aperture has two tritium inserts for fast sight pickup. Steel, post front sight has single, glowing tritium dot that puts you on target fast in daylight or darkness. Glass lamps, sealed in aluminum cylinders with polished sapphire windows for a crisp outline of light.

SPECS: Steel, matte finish, black. Fits plain barrel Rem. 870, 1100 and 11-87. Can be adapted to other models. Requires drilling and tapping receiver. Front sight epoxies over factory sight. Includes epoxy.

| #892-004-004 | Shotgun Adjustable Night Sights, | |
|--------------|----------------------------------|----------|
| | 2H00CTC | \$ 99.99 |

6 fits Browning Citori Hunter.

| #638-000-016 | Red Spark II Sight, 8C8K79 | \$ 10.99 |
|--------------|------------------------------|----------|
| #638-000-088 | Green Spark II Sight, 8C8G79 | 10.99 |

MAGNI-COMP SIGHT - Innovative tunnel sight with highly visible red or green rod provides exceptional sight contrast in all light conditions. Front sight dot is only visible when using correct head alignment, forcing proper shooting form and increasing accura-



cy. Red or green fiber optic rods are easily interchanged allowing you to change sight color when light conditions change. Designed to fit ventilated ribs with removable front beads. Contains a compact, stainless steel base that is secured firmly to the ventilated rib using included screw, making it ideal for heavy recoil loads or ported barrels. Sight base uses a locking spring to keep the light rod secure, yet allows easy interchangability of the red or green rod in the field with provided key. Includes five different size sight screws for a variety of ribs.

SPECS: Base - 1704 stainless steel, matte black finish, 11/4" (3.1cm) long. Rods – polymer, (1) red, (1) green, 11/16" (17.8mm) long x .07" (1.8mm) dia. Includes five screw sizes: 3-56" fits Winchester, Beretta, Benelli, and Ruger shotguns; M3 x .5" fits Browning BPS, Gold and Citori Field guns; M3 x .6" fits Browning Citori Hunter; 5-40" fits Mossberg shotguns; 6-48" fits Ithaca, Remington, and SKB field models.

#638-000-072 Magni-Comp, 8C29D74...... \$34.99

order on the web

VANG COMP SYSTEMS REM 870/1100/11-87 **GHOST RING SIGHTS**

Extremely Rugged; **Provides Fast Target Acquisition**

Heavy duty Picatinny rail with integral ghost ring sight naturally centers for fast target acquisition during

tactical ops. Front sight features a blade with white dot and solid steel side guards for maximum protection. Aperature is fully adjustable

for windage and elevation using clearly marked adjustment screws that hold under heavy recoil. Front sight is adjustable for elevation with included tool. Rail allows mounting or scopes and red dot

sights. Designed for non-ribbed barrels. SPECS: Fits Remington 870/1100/11-87 shotguns with non-ribbed barrels. Front sight requires soldering with Silvaloy 355 (not included). Ghost ring/rail requires drilling and tapping receiver for 8-40 tpi screws. Includes mounting hardware and instructions. **Front Sight** - Steel, in-the-white, .110" (2.8mm) diameter white dot. Ghost Ring/Rail - One-piece, hard anodized aluminum sight body and rail. 2.2 oz.(62.4g) weight. Rail - 23/4" (7cm) long x .830" (21mm) wide. Aperature - Steel, black. .23" (5.8mm) I.D. .5" (mm) high from top of receiver to center of aperature.

| #100-003-640 | Rem. 870/1100/11-87 Ghost Ring Front Sights, 6K82M44 | \$ 96.99 |
|--------------|--|----------|
| #100-004-335 | Rear Ghost Ring Sight w/Rail, 6K173H69 | 192.99 |

TRUGLO TRU-POINT XTREME **SHOTGUN SIGHT SET**

Fast & Accurate Sighting

Fiber optic sight brings your eye quickly to the sight in all light conditions. Improves accuracy for slug and turkey guns. Contrasting red front and green rear fiber optic rods are easy to locate in low-light. All steel front and rear sights clamp solidly to rib. Maintains sight settings,



prevents shifting under recoil. Adjustable for windage and elevation. Magnum Pro Gobble Dot features a conventional rifle-style rear sight with square notch that works well in most light conditions. Models available for .250" and .357" wide ventilated ribs. Tru-Point **Xtreme** features a rear sight that includes a square notch sight blade and an easily interchangeable ghost ring. Fits all shotguns equipped with 1/4", 5/16", or 3/8" wide ventilated ribs.

SPECS: Magnum Pro Gobble Dot - Steel, black. Front Sight - 1.4" (3.5cm) long. Rod - Polymer, red, "5/s" (23.6mm) long x .029" (.7mm) dia. Rear Sight - 1.4" long. Rod - Green, .035" (.89mm) dia. Tru-Point Xtreme - Aluminum, anodized, matte black. Front Sight - 15/16" (3.3cm) long. Rod - Red, 1" (2.5cm) long x .060" (1.5mm) dia. Rear Sight - 17/16" (3.6cm) long. Ghost Ring - 1/4" (6.4mm) I.D. Rods - Green, .029" (.7mm) dia. Fits 1/4" (6.4 mm), 5/16", or 3/8" wide ventilated ribs.

| #902-000-002 | .250" Magnum Pro Sight, 2K47H69 | \$ 52.99 |
|--------------|-----------------------------------|----------|
| #902-000-003 | .375" Magnum Pro Sight, 2K45K89 | 53.99 |
| #902-000-028 | Benelli Magnum Pro Sight, 2K45C89 | 53.99 |
| #902-000-119 | Tru-Point Xtreme Sight, 2K36E54 | 42.99 |
| | | |

WILLIAMS SHOTGUN SHORTY RAMP



Mounts Rifle Sights On Plain Barrel Shotguns

Steel. screw-on/solder-on ramps with stan-

dard 3/8" dovetail and a checkered rear surface to cut glare. .4375" radius designed for 12 gauge barrels with .875" outside diameter. SPECS: Steel, blued, matte finish. 13/4" (4.4cm) long x .612" (15.5mm) wide. Height - 3/16" (4.7mm). Accepts narrow ramp sight blades.

| #962-011-187 | Shorty Ramp, 3/16", | 2F22F94 | \$ 26.99 |
|--------------|---------------------|---------|----------|
|--------------|---------------------|---------|----------|

WILLIAMS UNIVERSAL "SLUGGER" FIRE SIGHT

Quickly Turns Rib-Equipped Shotguns Into Slug Guns

Give your favorite shotgun a more accurate, rifle-style sight picture in only minutes. Clamps



#962-000-014 Universal Slugger Fire Sight, 2F29A74. \$ 34.99

SHOTGUN FIRE SIGHTS - Models for Remington 870/1100 (pre-2003) and Winchester 1300 guns equipped with slug or turkey barrels and factory sight



bases. Front sight provides a glowing red dot that's easily seen in all ambient light conditions. Fully adjustable, U-notch rear has two glowing green dots for precise sight alignment.

ŠPECS: Machined aluminum, black, anodized. Rear - "U" notch fiber optic. Front - Fluorescent red front bead on sheared-style blade. Includes instructions. **Remington** fits Remington shotguns with 3/8" dovetail front sight ramp.

| #962-565-300 | Remington Fire Sights, | 2F24A64 | \$ 28.99 |
|--------------|-------------------------|---------|----------|
| #962-000-002 | Winchester Fire Sights, | 2F27M19 | 31.99 |

REMINGTON GHOST RING FIRE SIGHTS -

Bright, high contrast fiber optic sights with large aperture, rear ghost ring provide fast, accurate sight alignment in all light conditions. The more light, the brighter the beads glow. Front sight has a single red insert, rear ghost ring has two green inserts to form an easy-to-align, 3-dot sight picture. Fits Rem-

ington shotguns with 3/8" dovetail front sight ramp. 트 SPECS: Steel front 3/8" dovetail sight. Aluminum rear sight. Black, matte finish. Fiber optic insert. Bead - 1/16" (1.6mm) dia. Ghost Ring - .15" (3.8mm) dia. aperature.

#962-000-083 2003 & Earlier Ghost Ring Fire Sights,

BROWNELLS SIGHT CALCULATOR

TRY THE ONLINE SIGHT CALCULATORS

Automatically calculate SIGHT CORRECTION or front and rear SIGHT HEIGHT

Visit our website at www.brownells.com/sightcalculator

WILSON COMBAT REMINGTON 870/1100/11-87 SCATTERGUN TRAK-LOCK GHOST **RING SIGHT SET**



Tritium Front Sight Dot Lines Up With the Rear Ghost Ring Quickly for **FAST, Accurate Shooting**

In use with law enforcement agencies all over the world, this classic ghost-ring setup gives you fast sight acquisition and better ac-

curacy potential from your tactical scattergun. This rugged sight set is fully machined from bar stock steel, and allows quick adjustment of both elevation and windage with a single hex head screw. Easy to install, complete instructions included. Fits most 12 gauge Remington 870, 1100, and 11-87 models.

#965-000-359 Trak-Lock II Ghost Ring Sight Set,

w/735" Tritium Front, 5F107C29......\$ 114.95

XS SIGHT SYSTEMS REMINGTON SHOTGUN TACTICAL FRONT SIGHT

Speeds Sight Acquisition

Convert your shotgun to a tactical workhorse. Banded front sight features green Tritium dot surrounded by a white ring. Supplied shims ensure barrel band clamps snugly around muzzle. Contoured

rear sight requires drilling and tapping; includes two interchangeable aperture sizes.

SPECS: Steel, black, matte finish. Tritium dot with white ring, 3/4" (19mm) high from top of barrel. Fits Rem 870, 1100, 11-87 shotguns with .860-.885" (21.8-22.5mm) muzzle diameters.

#006-000-118 Banded Front Sight, only, 6K80F99 . . \$ 89.99

XS SIGHT SYSTEMS MOSSBERG 500/590/930 SHOTRAIL

Gives Your Shotgun A Rifle-Style Sight Picture

Easy-to-install tactical sight set has a Picatinny-rail section with ghost ring rear

sight and banded front sight. Picatinny rail is pre-drilled for factory optic mount holes. Ghost ring is adjustable for windage and elevation. Banded front sight post has a Tritium dot for visibility in all light conditions. Fits barrels less than 8.860" in diameter that do not have a front sight rib or base. 💻

SPECS: Picatinny Rail – Aluminum, anodized, black. Front/Rear Sights -Stress-proof steel, black oxide finish, Fits barrels with .840" to .860" O.D.

#006-000-185 (a) Mossberg 500/590/930 ShotRail,

XS SIGHT SYSTEMS SHOTGUN **BIG DOT TRITIUM FRONT SIGHT**



Installs Easily Over The Existing Bead Sight

High-visibility Tritium dot front sight surrounded by a

large white ring helps improve target focus and low light sight acquisition and sight recovery after muzzle flash. Installs over existing front sight beads from .125" - .140" diameter by filling the cavity on the underside of the sight with Brownells Acraglas Gel, then pressing the sight over the bead and allowing it to fully cure. If existing bead is too small or too large, replace with Brownells #6 bead for 3-56 threads or #26 for 6-48 threads. Some shotgun barrels may require drilling and tapping of existing hole to 6-48 for installation of #26 Brownells bead. **Remington Pedestal** model with stepped bottom fits Remington shotgun barrels with front sight pedestal. Vent Rib model with flat bottom fits shotgun barrels with ventilated ribs. Plain Barrel model with cupped bottom fits round shotgun barrels. Includes instructions.

SPECS: Machined steel, black, matte finish. Big Dot .161" (4mm) diameter. Fits beads from .125" (3.2mm) to .140" (3.5mm). Remington Pedestal fits Remington front sight pedestals. Vent Rib fits ventilated ribs. Plain Barrel fits round barrels. Includes instructions.

#006-000-158 (Remington Pedestal Big Dot Tritiuim, 6K57L59.....\$ 63.99

#006-000-159 Vent Rib Big Dot Tritium, 6K57A59.... #006-000-160 Plain Barrel Big Dot Tritium, 6K57F59...



GUARANTEED. FOREVER.® **SINCE 1939**